Vixrtex Wallcoverings®
A Division of RJF International Corporation
3875 Embassy Parkway
Fairlawn, OH 44333

VICRTEX WALLCOVERINGS®

FACT SHEET

Pattern Name: QUEST©

QUIK SPEC	U.S. UNITS	METRIC UNITS
Total Weight	15.0 oz./ linear yard	465 g./ linear meter
	10.0 oz./square yard	339 g./square meter
Roll Width	53/54 in.	135/137 cm.
Thickness	0.0067 in.	0.17 mm.
Fabric: Non Woven	Federal Spec: CCC-W-408A, Type I	CFFA Spec: CFFA-W-101C Type I, Class A
Fire Testing	NFPA 101® Life Safety Code®	
	NFPA 255 (ASTM E84, CAN S102M) Tunnel Test[1]: Class A Rating	U.L. Labeled and Listed
	NFPA 286 Corner Burn Test[2]: Meets requirements for Flame spread smoke developed and flashover	
Repeat	Vertical: N/A	Horizontal: N/A

1. When tested on GRC board with A-848-B adhesive
2. When tested on 5/8" type-x gypsum board with A-848-B adhesive

COLORLINE	PATTERN NUMBER/NAME OF COLORS

DESCRIPTION OF THE PATTERN: A lightweight version of our classic Dakota pattern.

Available in 5 colorways.

HANGING INSTRUCTIONS: Match: Random Match Reverse Strips: Yes

SPECIAL INSTRUCTIONS (if any):

QU15-01

QU15-07

QU15-11

QU15-22

QU15-58