

jolie atelier

Sanitas Wallcoverings are manufactured by:
RJF International Corporation
3875 Embassy Parkway
Fairlawn, Ohio 44333

Sanitas Wallcoverings
FACT SHEET
Pattern Name: Proxy

QUIK SPEC	U.S. UNITS:	METRIC UNITS:
Total Weight:	21 oz. PLY	651 g. PLM
	14 oz. PSY	475 g. PSM
Roll Width:	54/55 in.	139/142 cm.
Gauge (average):	0.020 in.	0.51 mm.
Fabric:	Non-woven	
Tensile (minimum):	50 x 55 lb _f	222 x 245 N
Tear (minimum):	25 x 25	---
Federal Spec:	CCC-W-408A, Type II	---
CFFA Spec:	CFFA-W-101D, Type II	---
Fire Testing:	NFPA 101 [®] Life Safety Code [®] NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ - Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover U.L. Listed and Labeled	
Repeat: Horizontal	27.0 in.	68.7 cm
Vertical	22.5 in.	57.3 cm
Nominal Pattern Width:	54"	
Hanging Instructions:	Non-reverse – Straight Match	
1. When tested on GRC board with A-848-B adhesive 2. When tested on 5/8" type X gypsum board with A-848-B adhesive		

COLORLINE

5 Colorways

Pattern Description: Playful, contemporary geometric texture.

JM12-36 Sundance	JM12-17 Biscuit	JM12-09 Flaxen
JM12-29 Woodstock Tan	JM12-82 Misty Moors	Note: Can be cut to 27" width.

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.