jolie atelier

QUIK SPEC

Total Waight

Sanitas Wallcoverings are manufactured by: RJF International Corporation 3875 Embassy Parkway Fairlawn, Ohio 44333

Sanitas Wallcoverings FACT SHEET

Pattern Name: Positively Square

METRIC UNITS:

Total weight.	21 0Z. FL 1	OST g. PLIVI
	14 oz. PSY	475 g. PSM
Roll Width:	55/56 in.	139/142 cm.
Causa (anongsa).	0.010 in	0.49 mm

U.S. UNITS:

Gauge (average): 0.019 in. 0.48 mm. Fabric: Non-woven 50 x 55 lb_f Tensile (minimum): 222 x 245 N Tear (minimum): 25 x 25 CCC-W-408A, Type II Federal Spec: CFFA-W-101D, Type II CFFA Spec: ---Fire Testing:

NFPA 101[®] Life Safety Code[®] NFPA 255 (UL723, CAN S102M) Tunnel Test¹

- Class A Rating
NFPA 286 Corner Burn Test²
Meets requirements for Flame Spread, Smoke Developed

and Flashover

	U.L. Listed and Labeled	
Repeat: Horizontal	6.75 in.	17.1 cm
Vertical	10.75 in.	28.0 cm
Nominal Pattern Width:	54"	
Hanging Instructions:	Reverse – Straight Match	

1. When tested on GRC board with A-848-B adhesive

2. When tested on 5/8" type X gypsum board with A-848-B adhesive

COLORLINE 7 Colorways

Pattern Description: Larger geometric squares on squares.

t union 2 escription. Zurger geometrie squares on squares.		
JM10-43 Ginger Spice	JM10-87 Glade	JM10-89 Lakeside
JM10-71 Grey Amethyst	JM10-22 Mountain Mist	
JM10-80 Riverstone	JM10-38 Strawmat	Note: Can not be cut to 27."

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.