QUIK SPEC	U.S. UNITS	METRIC UNITS
Total Weight:	21 oz. PLY	651 g. PLM
	14 oz. PSY	474 g. PSM
Roll Width:	52/54 in.	132/137 cm.
Gauge (average):	0.025 in.	0.64 mm.
Fabric:	Osnaburg	
Tensile (minimum):	50 x 55 lb$_f$	222 x 245 N
Tear (minimum):	25 x 25	
Federal Spec:	CCC-W-408A, Type II	
CFFA Spec:	CFFA-W-101D, Type II	
Fire Testing:	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84 CAN S102M) Tunnel Test[1] - Class A Rating NFPA 286 Corner Burn Test[2] Meets requirements for Flame Spread, Smoke Developed and Flashover U.L. Listed and Labeled	
Repeat: Horizontal	N.A.	
:Vertical	N.A.	
Nominal Pattern Width:	51 in.	130 cm
Hanging Instructions:	Random – Reverse	

1. *When tested on GRC board with A-848-B adhesive*
2. *When tested on 5/8" type X gypsum board with Koroseal® A-848-B adhesive*

COLORLINE   **16 Colorways**

This 'lizagator' pattern and emboss has wonderful detail and depth. Intrigue reflects the luxurious fashions of 1940's couture accessories**.**

2N21-92 Secrets	2N21-10 Intermingle	2N21-86 Lavish
2N21-33 Liaisons	2N21-39 Operator	2N21-99 Midnight
2N21-02 Undercover	2N21-56 Rendez-vous	2N21-43 Clandestine
2N21-18 Clueless	2N21-90 Translucent	2N21-65 Slingback
2N21-28 Fascination	2N21-74 Palatial	2N21-97 Allure
	2N21-61 Rogue	

<u>*Notes:*</u>
- *"Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.*
- *"Gauge" is the product thickness measured after the first pattern colorway is produced.*
- *"Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.*
- *"Nominal Pattern Width" is the expected width yield from one drop on the wall.*