

Sanitas Wallcoverings are manufactured by: **RJF International Corporation** 3875 Embassy Parkway Fairlawn, Ohio 44333

Sanitas Wallcoverings FACT SHEET

Pattern Name: La Spinetta©

QUIK SPEC	U.S. UNITS	METRIC UNITS
Total Weight:	21 oz. PLY	651 g. PLM
	14 oz. PSY	474 g. PSM
Roll Width:	53/55 in.	134/140 cm.
Gauge (average):	0.024 in.	0.61 mm.
Fabric:	Osnaburg	
Tensile (minimum):	50 x 55 lb _f	222 x 245 N
Tear (minimum):	25 x 25	
Federal Spec:	CCC-W-408A, Type II	
CFFA Spec:	CFFA-W-101D, Type II	
Fire Testing:	NFPA 101 [®] Life Safety Code [®]	
	NFPA 255 (ASTM E-84 CAN S102M) Tunnel Test ¹	
	- Class A Rating	
	NFPA 286 Corner Burn Test ²	
	Meets requirements for Flame Spread, Smoke Developed	
	and Flashover	
	U.L. Listed and Labeled	
Repeat: Horizontal	N/A	
:Vertical	N/A	
Nominal Pattern Width:	52 in.	132 cm
Special Instructions (if		
any):		
Hanging Instructions:	Random (Reverse)	
1. When tested on GRC be	pard with A-848-B adhesive	

2. When tested on 5/8" type X gypsum board with Koroseal® A-848-B adhesive

COLORLINE (PATTERN NUMBER/NAME OF COLORS)

Available in 16 colors

Pattern Description: Inspired by fields of waving grass discovered on a country drive, bring the outdoors inside.

1L21-14 Mont St. John	1L21-53 Bacio D'ivino*	1L21-43 Madrigal
1L21-27 Bianco	1L21-39 Wing Canyon	1L21-16 Quattro
1L21-85 Paloma	1L21-20 Silverado	1L21- 32 Opus One
1L21-72 Robledo	1L21-34 Viansa	1L21-25 Beringer
1L21-06 Sterling	1L21-59 L'uvaggio*	1L21-10 St. Supery
	1L21-51 Mayacamas	

^{*}These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners (ex. Lestoil®) have the potential to damage the surface of the wallcovering along with excessive scrubbing.

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.