

Koroseal Interior Products Group RJF International Corporation 3875 Embassy Parkway Fairlawn, Ohio 44333

FACT SHEET Sondra Alexander Couture Pattern Name: Indulgence (recolored 2009)

QUIK SPEC	U.S. UNITS	METRIC UNITS	
Total Weight:	21 oz. PLY	651 g. PLM	
	14 oz. PSY	474 g. PSM	
Roll Width:	54.5/55.5 in.	138/141 cm.	
Gauge (average):	0.020 in.	0.51 mm.	
Fabric:	Osnaburg		
Tensile (minimum):	50 x 55 lb _f	222 x 245 N	
Tear (minimum):	25 x 25		
Federal Spec:	CCC-W-408A, Type II		
CFFA Spec:	CFFA-W-101D, Type II		
Fire Testing:	NFPA 101 [®] Life Safety Code [®]		
	NFPA 255 (ASTM E-84 CAN S102M) Tunnel Test ¹		
	- Class A Rating		
	NFPA 286 Corner Burn Test ²		
	Meets requirements for Flame Spread, Smoke Developed		
	and Flashover		
	U.L. Listed and Labeled		
Repeat: Horizontal	6.0 in.	15.3 cm	
Vertical	8.13 in.	20.7 cm	
Hanging Instructions:	Match Blocks (Reverse)		
1. When tested on GRC is	poard with A-848-B adhesive		
2. When tested on 5/8" t	ype X gypsum board with Korosea	$l^{\mathscr{B}}A$ -848-B adhesive	

COLORLINE 23 Colorways

Gorgeous leather texture stitched in 6x8" rectangles – couture for the walls!

Congeous reading tentanges in one rectangles couldness wants.		
3B21-11 Artemesia	3B21-48 Lucca*	3B21-93 Corso Como*
3B21-30 Livia	3B21-55 V. Adriana	3B21-51 Alessandro
3B21-13 Ostia Antica	3B21-84 Palladio	3B21-53 Piazzo de Spagno
3B21-19 Capitoline	3B21-68 Borghese	3B21-94 Di Corsano*
3B21-08 Augustus	3B21-73 Amalfi*	3B21-35 Val di Pesa
3B21-04 Aventine	3B21-56 Alberese	3B21-60 Positano
3B21-29 Via Appia	3B21-52 S. Sophia	3B21-99 La Pampas
3B21-43 Via Condotti		3B21-40 Sorrento

^{*}These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners (ex. Lestoil®) have the potential to damage the surface of the wallcovering along with excessive scrubbing.

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.