Studios Maya VinylsTM

3875 Embassy Parkway Fairlawn, OH 44333

(800) 828-4556 www.koroseal.com



A subtle pattern and coloration that move with the light. Grassweave feels and looks like a natural grasscloth but is strong enough for the highest traffic areas.

		US UNITS	METRIC UNITS	
Total Weigh	t	21.0 oz PLY 14.0 oz PSY	651 g PLM 474 g PSM	
Roll Width		54 in.	137 cm	
Gauge		23 Mils	0.58 mm	
Fabric		Osnaburg		
Tensile (Minimum)		50 x 55 lb _f	222 x 245 N	
Tear (Minimum)		25 x 25		
Federal Spec		CCC-W-408A, Type II		
CFFA Spec		CFFA-W-101-D, Type II		
Fire Testing		NFPA 101 [®] Life Safety Code [®] NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover UL Labeled and Listed		
Repeat	Vertical Horizontal Match Information	N/A N/A Random Match, Reverse	e Hang	
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive		

Available in 14 Colorways

GW21-54	Cabernet	*GW21-40	Gunmetal
GW21-34	Champagne	GW21-17	Linen
*GW21-66		GW21-05	Natural Linen
GW21-49	Desert Paint	GW21-38	Natural Silk
*GW21-29	Golden Cloth	*GW21-98	Silver
GW21-57	Golden Copper	GW21-12	Spring Wheat
GW21-84	Green Bamboo	GW21-43	Vanilla Bean

^{*} These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners (ex. Lestoil®) have the potential to damage the surface of the wallcovering along with excessive scrubbing