

Sanitas Wallcoverings are manufactured by: RJF International Corporation 3875 Embassy Parkway Fairlawn, Ohio 44333

Sanitas Wallcoverings FACT SHEET

Pattern Name: Excess©

QUIK SPEC	U.S. UNITS	METRIC UNITS	
Total Weight:	21 oz. PLY	651 g. PLM	
	14 oz. PSY	474 g. PSM	
Roll Width:	53/55 in.	135/140 cm.	
Gauge (average):	0.020 in.	0.51 mm.	
Fabric:	Osnaburg		
Tensile (minimum):	50 x 55 lb _f	222 x 245 N	
Tear (minimum):	25 x 25		
Federal Spec:	CCC-W-408A, Type II		
CFFA Spec:	CFFA-W-101D, Type II		
Fire Testing:	NFPA 101 [®] Life Safety Code [®]		
	NFPA 255 (ASTM E-84 CAN S102M) Tunnel Test ¹		
	- Class A Rating		
	NFPA 286 Corner Burn Test ²		
	Meets requirements for Flame Spread, Smoke Developed		
	and Flashover		
	U.L. Listed and Labeled		
Repeat: Horizontal	17.25 in.	43.8 cm	
:Vertical	17.00 in.	43.2 cm	
Nominal Pattern Width:	51.75 in.	131.4 cm	
Special Instructions (if		·	
any):			
Hanging Instructions:	Match Blocks (Reverse)		

1. When tested on GRC board with A-848-B adhesive

2. When tested on 5/8" type X gypsum board with Koroseal® A-848-B adhesive

COLORLINE (PATTERN NUMBER/NAME OF COLORS)

17 Colorways

The architecture of leather done to Excess - 17" stitched squares in timeless, classic, irresistible colors.

3E21-34 Luscious	3E21-92 Ice Queen	3E21-93 Star Africa*
3E21-19 Vicuna	3E21-99 Desire	3E21-87 Irreverent
3E21-29 Alpaca	3E21-41 Fabulous*	3E21-38 Kentucky Derby
3E21-06 Cashmere	3E21-80 Heiress	3E21-66 Beyond
3E21-55 Jet Set	3E21-62 Roulette	3E21-68 Vain
3E21-58 Sleek		3E21-51 Exotic

^{*}These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners (ex. Lestoil®) have the potential to damage the surface of the wallcovering along with excessive scrubbing.

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.