

Sanitas Wallcoverings are manufactured by: RJF International Corporation 3875 Embassy Parkway Fairlawn, Ohio 44333

Sanitas Wallcoverings FACT SHEET

Pattern Name: Sakima

QUIK SPEC	U.S. UNITS:	METRIC UNITS:		
Total Weight:	21 oz. PLY	651 g. PLM		
	14 oz. PSY	475 g. PSM		
Roll Width:	52/54 in.	132/137 cm.		
Gauge (average):	0.019 in.	0.48 mm.		
Fabric:	Osnaburg			
Tensile (minimum):	50 x 55 lb _f	222 x 245 N		
Tear (minimum):	25 x 25			
Federal Spec:	CCC-W-408A, Type II			
CFFA Spec:	CFFA-W-101D, Type II			
Fire Testing:	NFPA 101 [®] Life Safety Code [®]			
	NFPA 255 (UL723, CAN S102M) Tunnel Test ¹			
	- Class A Rating			
	NFPA 286 Corner Burn Test ²			
	Meets requirements for Flan	me Spread, Smoke Developed		
	and Flashover			
	U.L. List	ted and Labeled		
Repeat: Horizontal	N.A.	N.A.		
Vertical	N.A.	N.A.		
Nominal Pattern Width:	51in.	130 cm.		
Hanging Instructions:	Random Reverse			
Special Instructions:		-		
1. When tested on GRC board with A-848-B adhesive				
2. When tested on 5/6	8" type X gypsum board with A-848-E	3 adhesive		

COLORLINE 16 Colorways

Pattern Description: Hand-painted watercolor diamond-like drapery or serpent skin?

2K21-12 Mayan	2K21-38 Sahara	2K21-47 Panama	2K21-67 Amazon
2K21-27 Rio	2K21-42 Montezuma	2K21-73 Cheyenne	2K21-63 Sedona
2K21-33 Yuma	2K21-89 Dakota	2K21-81 Galapagos	2K21-40 Laramie
2K21-85 Belize	2K21-96 Caribe	2K21-49 Sierra	2K21-51 Azteca

Notes:

- "Pattern Width" is the trim width on the specification and represents the width of the wallcovering that will be received by the customer.
- "Gauge" is the product thickness measured after the first pattern colorway is produced.
- "Tensile" and "Tear" results are the minimums required by CCC-W-408A federal specifications.
- "Nominal Pattern Width" is the expected width yield from one drop on the wall.