

# Plan A

## P/6677 Cinch

<b>Construction</b>	Tufted, Textured Loop Pile
<b>Face Fiber</b>	100% Milliken-Certified WearOn® Type 6,6 Nylon
<b>Stain Repel / Stain Resist / Soil Release</b>	StainSmart®
<b>Antimicrobial</b>	AlphaSan® Built-In Protection
<b>Dye Method</b>	DCP (Digital Color Placement)
<b>Finished Face Weight</b>	21 oz./sq.yd. (712.1 g./sq.m.)
<b>Gauge</b>	1/8 (31.5/10 cm.)
<b>Rows</b>	14.0/in. (55.1/10 cm.)
<b>Tufts</b>	112.0/sq.in. (1,735.7/100 sq.cm.)
<b>Finished Pile Height</b>	0.09 in. (2.3 mm.) avg.
<b>Density Factor</b>	543,994
<b>Average Density</b>	8,400
<b>Standard Backing</b>	PVC-Free Comfort Plus® ES cushion Available with TractionBack® Available with ESP cushion for NSF 140 Platinum certification With ESP Backing: 24% Pre-Consumer, 3% Post-Consumer With ESP Backing: 16% Pre-Consumer, 11% Post-Consumer
<b>Recycled Content by Total Product Weight</b>	
<b>Nominal Total Thickness</b>	0.36 in. (9.14 mm.)
<b>Tile Size</b>	50cm x 50cm (19.7 x 19.7 in.) 1m x 1m (39.4 x 39.4 in.)
<b>Nominal Total Weight</b>	109.7 oz./sq.yd. (3,719.6 g./sq.m.)
<b>Flammability (Radiant Panel ASTM-E-648)</b>	≥ 0.45 (Class I)
<b>Smoke Density (NFPA-258-T or ASTM-E-662)</b>	≤ 450
<b>Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)</b>	Self-Extinguishing
<b>Lightfastness (AATCC 16E)</b>	≥ 4.0 at 80 hrs.
<b>Crocking (AATCC 165)</b>	≥ 4.0 wet or dry
<b>Static Electricity (AATCC-134) 20% R.H., 70° F.</b>	≤ 3.5 KV, Permanent Conductive Fiber
<b>Dimensional Stability - Aachener Test (DIN Std 54318)</b>	≤ 0.2%
<b>Appearance Retention Rating (CRI TM101)</b>	Severe Use
<b>Recommended Maintenance</b>	MilliCare® Textile and Carpet Care Service Network
<b>Indoor Air Quality – CRI Green Label Plus™</b>	GLP0793, Carpet Category 5Y

Design Copyright – Milliken & Company

This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending.

Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.



### Warranties:

Lifetime Antimicrobial Protection (AlphaSan®)  
Lifetime Antistatic  
Lifetime Color Pattern Permanency  
Lifetime Cushion Resiliency  
Lifetime Delamination of Backing  
Lifetime Dimensional Stability  
Lifetime Edge Ravel

Lifetime Face Fiber Wear  
Lifetime Floor Compatibility  
Lifetime Floor Release  
Lifetime Moisture Resistance  
Lifetime Staining/Soiling (StainSmart®)  
Lifetime Tuft Bind  
Flammability

