


G3500VM Silhouette Handrail



- ▶ 77/8" (200mm) height x 1 1/2" (38mm) gripping diameter, extends 3 1/4" (82mm) from the wall
- ▶ Handrail is .080" (2mm) thick, scratch and stain resistant non-PVC cover
- ▶ Handrail available in 100 standard colors
- ▶ Lower wall guard has an aluminum wall thickness of .080" (2mm)
- ▶ Lower wall guard is available in 10 Metal Tone finish options
- ▶ Meets ADA and ANSI criteria
- ▶ Manufactured in 8' - 16' (2.44m - 4.88m) standard lengths
- ▶ All mounting fasteners are included with each order
- ▶ May qualify for LEED MR Credit 4.1 = 1 credit; MR Credit 4.2 = 1 credit



IPC.669/REV.1

P.O. Box 406 · Muskego, Wisconsin 53150 USA
inprocorp.com
Nationwide 800.222.5556/Fax 888.715.8407
International Sales 262.679.5521/Fax 262.679.5524

INPro
IPC Interior Protection Products
and Decorative Surfaces

G3500VM Silhouette Handrail

Suggested Specifications

PART 1 GENERAL

1.01 SUMMARY

- A. Handrail systems PVC free for pedestrian safety and wall protection

1.02 SECTIONS INCLUDES

- A. G3500VM Silhouette Handrail System, PVC free handrail with integrated aluminum wall guard

1.03 REFERENCES

- A. American National Standards Institute (ANSI)
B. American Society for Testing and Materials (ASTM)
C. American with Disabilities Act (ADA)
D. Environmental Protection Agency (EPA)
E. Kitchen Cabinets Manufacturers Association (KCMA)
F. National Emission Standards for Hazardous Air Pollutants (NESHAP)

- G. Society of Automotive Engineers (SAE)

1.04 SYSTEM DESCRIPTION

- A. Performance Requirements: Provide PVC free handrail systems with integrated wall guard that conform to the following requirements of regulatory agencies and the quality control of IPC Door and Wall Protection Systems, InPro Corporation.

1. Fire Performance Characteristics: Provide aluminum wall guard components conforming with NFPA Class A fire rating. Surface burning characteristics, as determined by ASTM E-84, shall be flame spread of 0 and smoke development of 5.
2. Fire Performance Characteristics: Provide PVC free profile material conforming with NFPA Class A fire rating. Surface burning characteristics, as determined by ASTM E-84, shall be flame spread of 10 and smoke development of 300.
4. Impact Strength: Provide PVC free profile materials that have an Impact Strength of 19 ft-lbs/inch of thickness as tested in accordance with the procedures specified in ASTM D-256-90b, Impact Resistance of Plastics.
5. Chemical and Stain Resistance: Provide PVC free profile materials that show resistance to stain when tested in accordance with applicable provisions of ASTM D-543.
6. Chemical and Stain Resistance: Provide powder coat materials that show resistance to stain when tested in accordance with applicable provisions of ASTM D-543.
7. Fungal and Bacterial Resistance: Provide powder coated metal components that do not support fungal or bacterial growth as tested in accordance with ASTM G-21 and ASTM G-22.
8. Fungal and Bacterial Resistance: Provide PVC free material that does not support fungal or bacterial growth as tested in accordance with ASTM G-21 and ASTM G-22.
9. Color Consistency: Provide components matched in accordance with SAE J-1545 - (Delta E) with a color difference no greater than 1.0 units using CIE Lab, CIE CMC, CIE LCh, Hunter Lab or similar color space scale systems.
10. Code Compliance: Provide handrails that comply with all current ANSI and ADA requirements.

1.05 SUBMITTALS

- A. Product Data: Manufacturer's printed product data for each product indicated in this section.

- B. Detail Drawings: Mounting details with appropriate fasteners for specific project substrates.

- C. Samples: Verification samples of handrail, 10" (254mm) long, in full size profiles with mounting brackets of each type indicated.

- D. Manufacturer's Installation Instructions: Printed installation instructions for each handrail.

1.06 DELIVERY, STORAGE AND HANDLING

- A. Deliver materials in unopened factory packaging to the jobsite.
- B. Inspect materials at delivery to assure that specified products have been received.
- C. Store in original packaging in a climate controlled environment away from direct sunlight.

1.07 WARRANTY

- A. Standard IPC limited lifetime warranty against material and manufacturing defects.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Acceptable Manufacturer: IPC Door and Wall Protection Systems, InPro Corporation, PO Box 406, Muskego, WI 53150 USA;
Telephone 800-543-1729, Fax: 888-715-8407,
Internet address: www.inprocorp.com
- B. Substitutions: Not permitted
- C. Provide all handrails and wall protection from a single manufacturer.

2.02 LEED CRITERIA

- A. Provide PVC free handrail systems with metal components that have recycled content.

1. MR CR4.1, 10% (post-consumer + 1/2 pre-consumer), 1 Credit

2. MR CR4.2, 20% (post-consumer + 1/2 pre-consumer), 1 Credit

2.03 MANUFACTURED UNITS

- A. PVC free/Aluminum Handrail System

1. G3500VM Silhouette Handrail, 7-7/8" (200mm) height x 1-1/2" (38mm) gripping diameter, system extends 3-1/4" (83mm) from the wall. System includes 1-1/2" (38mm) diameter PVC free cover/aluminum retainer, handrail and an integrated 5" (127mm) aluminum wall guard.

2.04 MATERIALS

- A. Polycarbonate/acrylonitrile butadiene styrene (PC/ABS):

1. Extruded PC/ABS: Snap-on handrail covers of .080" (2mm) thickness shall be extruded from chemical and stain resistant PC/ABS

- B. Acrylonitrile butadiene styrene (ABS)

1. Molded components: Handrail returns and corners shall be made of chemical and stain resistant ABS.

- C. Aluminum

1. Continuous aluminum retainer of .080" (2mm) thickness shall be fabricated from 6063-T5 aluminum with a mill finish.

2. Continuous aluminum wall guard of .080" (2mm) thickness shall be fabricated from 6063-T5 aluminum with a powder coat finish.

3. Cast Aluminum: Wall guard returns and corners shall be fabricated from die cast aluminum.

- D. Stainless Steel

1. Stainless steel brackets shall be #4 satin finish.

2.05 COMPONENTS

- A. Wall guard returns and corners shall be cast aluminum and a finish/color to match wall guard.

- B. Molded handrail returns, corners and brackets shall be made of injection molded ABS.

- C. Stainless steel bracket shall be fabricated from cast stainless steel with a brushed finish or a solid color powder coat metal tone finish.

- D. Fasteners: All mounting systems accessories appropriate for substrates indicated on the drawings shall be provided.

2.06 FINISHES

- A. PVC free Covers: Color of the handrail PVC free cover to be selected, by the architect, from the IPC finish selection. Surface shall have a pebble texture.

- B. Wall guard color: Color of the wall guard to be selected by the architect from the InPro Corporation metal tone color palette.

- C. Stainless Steel Brackets

1. Color of the stainless steel bracket to be selected by the architect from the solid color metal tone color palette.

2. Color of stainless steel brackets shall be #4 satin finish stainless steel.

- D. Molded Components: Molded handrail returns and corners shall be of a color matching the handrail. Surface shall have a pebble texture. Molded bracket components shall be a color matching the wall guard. Surface shall have a pebble texture.

PART 3 EXECUTION

3.01 INSTALLERS

- A. Installer should be familiar with the installation of fine finished wood products.

3.02 EXAMINATION

- A. Examine areas and conditions in which handrail will be installed.

1. Complete all finishing operations, including painting, before beginning installation of handrail system materials.

2. Wall surface shall be dry and free from dirt, grease and loose paint.

3.03 PREPARATION

- A. General: Prior to installation, clean substrate to remove dust, debris and loose particles.

3.04 INSTALLATION

- A. General: Locate the handrail as indicated on the approved detail drawing for the appropriate substrate and in compliance with the IPC installation instructions. Install handrail level and plumb at the height indicated on the drawings.

3.05 CLEANING

- A. At completion of the installation, clean surfaces in accordance with the IPC clean-up and maintenance instructions.

