

TEST REPORT

DATE: 04/12/2008	TEST NUMBER: 113474
CHENT	TECT ITOMBER. 110474

		TEST NOWIDER.	1104/4
CLIENT	Masland Carpets		

TEST METHOD CONDUCTED	Aachen - (Dimensional Stability Evaluation)	72
-----------------------	---	----

DESCRIPTION OF TEST SAMPLE				
IDENTIFICATION	T423 Brush Strokes			
COLOR	04201 Batik			
ROLL				
CONSTRUCTION	Multi-Level Loop Pile			
FIBER	·			
BACKING	TL			
REFERENCE				

GENERAL PRINCIPLE

This test is designed to examine dimensional changes in textile floor coverings due to various conditions of heat and moisture. Measurements are taken in the length and cross directions of the test sample after each treatment. A change in the dimension of the test sample is calculated as a percentage of the original preconditioned sample measurement. Shrinkage is indicated by a negative quotation while expansion is indicated by a positive quotation.

TEST RESULTS

	Measurement	Percent		Measurement	Percent
Mo	24.0125		C ₀	24.0360	
MT1	24.0025	-0.042%	CTI	24.0270	-0.037%
M _{T2}	24.0035	-0.037%	C _{T2}	24.0245	-0.048%
Мтз	24.0055	-0.029%	Стз	24.0315	-0.019%
M _{T4}	24.0095	-0.012%	C _{T4}	24.0305	-0.023%

- Mo
 Original measurement in machine direction
 Co
 Original measurement in cross direction
- T₁ Two hours in drying oven at 60° C
- Two hours submerged in 0.1% detergent solution at 20°C
- T₃ Twenty four hours in drying oven at 60°C
- T₄ Forty eight hours conditioning at 20°C and 65% relative humidity

AVERAGE CHANGE MACHINE DIRECTION	-0.007 Inch	
AVERAGE CHANGE CROSS DIRECTION	-0.008 Inch	

APPROVED BY:

Lang aslung

This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical or similar products. This report, or the name of Professional Testing Laboratory, Inc., shall not be used under any circumstance in advertising to the general public.

714 Glenwood Place Dalton, GA 30721 706-226-3283 Fax: 706-226-6787 protest@optilink.us