Test Number: 254303



P.O. Box 1948

1503 Murray Ave.

Dalton, Georgia 30722-1948 • Phone 706-278-3013 • Fax 706-272-7057 • E-mail: ittslab@dalton.net

TEST REPORT

Customer: Masland Carpets, Inc.

July 29, 2005

Subject:

Specimens of the submitted sample were prepared and tested in accordance with the procedures proposed by the National Institute of Standards and Technology (formerly National Bureau of Standards), Technical Note 708 and NFPA 258, ASTM E 662-03.

SMOKE DENSITY TEST (NIST)

Operating Conditions

Irradiance:

2.5 watts/cm²

G Factor

#1

132

Thermal Exposure: Furnace Voltage:

Flaming 98

Burner Fuel:

Propane

Sample Description

Style: 7243 Random Control

Test Results

| Chamber Temperature, | °F (start) |
|----------------------|------------|
| Chamber Pressure | |

Minimum Transmittance (TM), %

at, minutes

Maximum Specific Optical Density (DM)

Clear Beam, (DC)

DM, CORRECTED (DMC)

Specific Optical Density at 1.5 minutes

Specific Optical Density at 4.0 minutes

Time to 90% DM, minutes

Time to DS = 16, minutes

| | <i>11</i> 1 | # L | πJ | Average |
|-----|-------------|----------------|--------------|---------|
| | 95 | 95 | 95 | |
| | Mair | ntained positi | ve, under 3' | " H₂O |
| | 72% | 48% | 58% | |
| | 9.60 | 8.20 | 9.00 | 8.90 |
| - 1 | 4 10 4 | 4-4 | | |

#2

#2

| 70 /0 | 3070 | |
|-------|---|---|
| 8.20 | 9.00 | 8.90 |
| 174 | 163 | 163 |
| 24 | 19 | 20 |
| 150 | 144 | 143 |
| 20 | 13 | 13 |
| 152 | 117 | 124 |
| 6.20 | 7.30 | 7.20 |
| 1.40 | 1.50 | 1.50 |
| | 8.20 174 24 150 20 152 6.20 | 8.20 9.00 174 163 24 19 150 144 20 13 152 117 6.20 7.30 |

L. Kent Suddeth

Executive Vice President