

TEST REPORT

DATE: 10/28/2009 TEST NUMBER: 124430

TEST METHOD CONDUCTED	Aachen - (Dimensional Stability Evaluation)
-----------------------	---

DESCRIPTION OF TEST SAMPLE				
IDENTIFICATION	T440 Solar			
COLOR	04133 Altair			
ROLL				
CONSTRUCTION	Loop Pile			
FIBER	Antron Lumena® Solution Dyed Nylon			
BACKING	Vinyl			
REFERENCE	GSA INITIAL GSA SIN #31-303			

GENERAL PRINCIPLE

This test is designed to examine dimensional changes in textile floor coverings due to various conditions of heat and moisture. Measurements are taken in the length and cross directions of the test sample after each treatment. A change in the dimension of the test sample is calculated as a percentage of the original preconditioned sample measurement. Shrinkage is indicated by a negative quotation while expansion is indicated by a positive quotation.

TEST RESULTS

	Measurement	Percent		Measurement	Percent
Mo	24.0090		C ₀	24.0385	
M _{T1}	23.8840	-0.521%	C _{T1}	24.0565	+0.075%
M _{T2}	24.0490	+0.167%	C _{T2}	24.0775	+0.162%
M _{T3}	24.0410	+0.133%	Стз	24.0505	+0.050%
M _{T4}	24.0305	+0.090%	C _{T4}	24.0430	+0.019%

Mο	Original measurement in machine direction
Co	Original measurement in cross direction

T₁ Two hours in drying oven at 60° C

T₂ Two hours submerged in 0.1% detergent solution at 20°C

T₃ Twenty four hours in drying oven at 60°C

T₄ Forty eight hours conditioning at 20°C and 65% relative humidity

Lang aflury

AVERAGE CHANGE MACHINE DIRECTION	-0.008 Inch	
AVERAGE CHANGE CROSS DIRECTION	+0.018 Inch	

APPROVED BY:

This report is provided for the exclusive use of the client to whom it is addressed. It may be used in its entirety to gain product acceptance from duly constituted authorities. This report applies only to those samples tested and is not necessarily indicative of apparently identical of similar products. This report, or the name of Professional Testing Laboratory Inc. shall not be used under any circumstance in advertising to the general public.

714 Glenwood Place Dalton, GA 30721 Phone: 706-226-3283 Fax: 706-226-6787 email: protest@optilink.us