

Logico ceiling
Logico mini ceiling
Logico micro ceiling
Logico nano ceiling

design

Michele De Lucchi
Gerhard Reichert
2001, 2002, 2003, 2006

Artemide[®]
www.artemide.net

Awards

Design Innovationen Design Zentrum
Nordrhein Westfalen
Reddot Design Award
2002 - Essen (Deutschland)

Light emission



Ceiling mounted luminaires for diffused incandescent or fluorescent lighting for applications with a single diffuser unit or with an assembly of three or four diffuser units in a linear or nested configuration; custom configurations available.

Materials: diffuser in handblown venetian glass with satined finish • diffuser(s) supporting frame and canopy in die-cast aluminum with pale grey matte lacquered finish • mounting to standard electrical junction boxes • newly redesigned to incorporate compact fluorescent option utilizing GU24 base with integrated ballast and lamp holder

Plafonniers à éclairage fluorescent ou incandescent diffus; installation simple ou multiple permettant l'assemblage de trois ou quatre plafonniers pour obtenir une configuration en rangée ou emboîtée; configurations personnalisées possibles.

Matériaux: diffuseur en verre soufflé à la main au fini extérieur satiné • support de diffuseur et monture en aluminium au fini laqué gris pâle • se fixe aux boîtes de connexion électrique standard • modèle repensé compatible avec les ampoules fluorescentes compactes, base GU24 avec ballast et douille de lampe intégrés

Luminarias de techo para iluminación incandescente o fluorescente difusa para utilizar con un solo difusor o con un conjunto de tres o cuatro difusores dispuestos de forma lineal o anidada; configuraciones personalizadas disponibles.

Materiales: difusor de vidrio veneciano soplado a mano con acabado satinado • soporte de difusor/es y cubierta de fundición de aluminio con acabado laqueado mate de color gris pálido • montaje en caja de conexiones eléctricas estándar • nuevo diseño que incorpora una opción fluorescente compacta, que utiliza la base GU24 con balasto y portalámpara integrados



Ristorante Il Corniolo, Cornaredo (Italy)
Photo: Miro Zagnoli



Logico ceiling



Logico micro quadruple nested ceiling



Artemide
www.artemide.net

Logico mini triple nested ceiling



Logico triple linear ceiling



12 3/4"
32.5 cm



15 3/4"
40 cm

15 3/4"
40 cm

Logico ceiling single

incandescent source

- 1 x 150W (E26/A21)


or

- 1 x 150W (E26/G40)


or

fluorescent source

- 1 x 26W (GX24q-3/T4)



13 3/4"
35 cm



15 3/4"
40 cm

max 39 1/4"
max 100 cm

Logico ceiling triple linear

incandescent source

- 3 x 150W (E26/A21)

or

- 3 x 150W (E26/G40)


or

fluorescent source

- 3 x 26W (GX24q-3/T4)



13 3/4"
35 cm



26"
66 cm

26"
66 cm

Logico ceiling triple nested

incandescent source

- 3 x 150W (E26/A21)

or

- 3 x 150W (E26/G40)

or

fluorescent source

- 3 x 26W (GX24q-3/T4)



9"
23 cm



11"
28 cm

11"
28 cm

Logico mini ceiling single

incandescent source

- 1 x 100W (E26/A19)

or

- 1 x 100W (E26/G25)

or

fluorescent source

- 1 x 18W (GX24q-2/T4)



9"
23 cm



11"
28 cm

max 26"
max 66 cm

Logico mini ceiling triple linear

incandescent source

- 3 x 100W (E26/A19)


or

- 3 x 100W (E26/G25)

or

fluorescent source

- 3 x 18W (GX24q-2/T4)



9"
23 cm



17 3/4"
45 cm

17 3/4"
45 cm

Logico mini ceiling triple nested

incandescent source

- 3 x 100W (E26/A19)

or

- 3 x 100W (E26/G25)

or

fluorescent source

- 3 x 18W (GX24q-2/T4)



9"
23 cm



17 3/4"
45 cm

23 13/16"
60.5 cm

Logico mini ceiling quadruple nested

incandescent source

- 4 x 100W (E26/A19)

or

- 4 x 100W (E26/G25)

or

fluorescent source

- 4 x 18W (GX24q-2/T4)



7 1/2"
19 cm




7"
18 cm

7"
18 cm

Logico micro ceiling single

incandescent source

- 1 x 60W (E12/G16 1/2)



8 1/4"
21 cm



7"
18 cm

19 1/4"
49 cm

Logico micro ceiling triple linear

incandescent source

- 3 x 60W (E12/G16 1/2)



8 1/4"
21 cm




13"
33 cm

13"
33 cm

Logico micro ceiling triple nested

incandescent source

- 3 x 60W (E12/G16 1/2)



8 1/4"
21 cm



13"
33 cm

17 3/4"
45 cm

Logico micro ceiling quadruple nested

incandescent source

- 4 x 60W (E12/G16 1/2)



5"
13 cm



4 1/4"
11 cm

4 1/4"
11 cm

Logico nano ceiling single

incandescent source

- 1 x 60W (E12/G16 1/2)



Examples of special projects.
Exemples de projets spéciaux.
Ejemplos de proyectos especiales.

