


Building Entrances
Doorways
Walkways
Accent and
General Lighting



BL-107



BL-106



BL-105

METRIC

BL

Specifications



Wall and Ceiling Mount

ADA



IP65

Certifications

The fixture shall be ETL and CETL listed for wet location and have a protection rating of IP65, dust-tight and jet-water proof. The fixture shall meet ADA requirements (BL-105 and BL-106). The fixture shall be wall and ceiling mount capable (BL-105 and BL-106).

Housing

The housing shall be constructed of die cast aluminum.

Ballast

The ballast shall be readily accessible, removable and insulated. The fixture is to be pre-wired and electronically tested before shipment.

Lens

The lens shall be opal polycarbonate. (BL-105 and BL-106).
The lens shall be clear glass (BL-107).

Hardware

All exposed hardware shall be stainless steel.

Finish

BK-BZ-WH-GR-GY-NA baked enamel standard, other colors available.

PROJECT
FIXTURE TYPE
CATALOG#

2930 South Fairview Street
 Santa Ana, CA 92704
 Phone: 714 668 3660
 Fax: 714 668 1107
 sales@allscape.net
 http://www.alllighting.com

BL-105/106/107

Product Order Guide


Series	Max Watts	Lamp Type	Voltage ¹	Finish ¹
BL-105	13 CF	CF ²	120	BK Black
BL-106	2(13) CF	CF ²	208	BZ Bronze
	26 CFQ	CFQ ²	240	WH White
	42 CFT	CFT ²	277	GR Green
				NA Natural Aluminum
				GY Gray
				CC Custom Color
BL-107	75 Halogen	T3mini		
	13 CF	CF ²		
	26 CFQ	CFQ ²		

¹ Consult factory for other colors and voltages


² CF = single biax, CFQ = double biax, CFT = triple biax

Example: BL-105-13CF-120-BK-PL


Photometric Data



BL-105-26CFQ-GL
 1,800 Lumens
 8.0 ft Mounting Height
 ISOLUX Curves - value in initial footcandles




BL-105-(2)13CF-GL
 1,720 Lumens
 8.0 ft Mounting Height
 ISOLUX Curves - value in initial footcandles




BL-107-13CF-BK
 860 Lumens
 8.0 ft Mounting Height
 ISOLUX Curves - value in initial footcandles

Luminaire Dimensions


Luminaire	A		B		B(large)		Weight	
	Inch	mm	Inch	mm	Inch	mm	lbs.	kg
BL-105	9.85	250	3.54	90	5.42	138	8.6	3.9
BL-106	9.85	250	3.94	100	5.82	148	8.6	3.9
BL-107	9.85	250	4.13	105	6.00	153	8.8	4.0



BL-105



BL-106



BL-107