

Building Entrances

Doorways

Walkways

Accent and

General Lighting



BL-125



BL-126



BL-127-UD Up/Downlight

DOWNLIGHTS 150

BL

Specifications



Certifications

The fixture shall be ETL and CETL listed for wet location and have a protection rating of IP65, dust-tight and jet-water proof.

Housing

The housing shall be constructed of extruded aluminum and cast aluminum door frames.

Ballast

The ballast shall be readily accessible, removable and insulated. The fixture is to be pre-wired and electronically tested before shipment.

Lens

The lens shall be clear tempered safety glass.

Reflector

The reflector shall be textured aluminum and silver anodized.

Mounting Detail

The fixture shall be pendant, ceiling or wall mounted.

Pendant mounting detail — supported by a 5/8" diameter aluminum pipe (specify length) with hang straight bracket (maximum 30° slope) and canopy for mounting to 4" octagon box. Mounting hardware by others.

Surface mounting detail — attached to ceiling through two 1/4" holes at 180° with 6-5/16" bolt circle. Mounting hardware by others.

Wall mounting detail — wall mounting plate is attached to wall through four 1/2" holes at 90° on a 6" h x 4" w bolt pattern to mount over 4" octagon box. Mounting hardware by others.

Hardware

All exposed hardware shall be stainless steel.

Finish

BK-BZ-WH-GR-GY-NA baked enamel standard, other colors available.

PROJECT
FIXTURE TYPE
CATALOG#

2930 South Fairview Street
 Santa Ana, CA 92704
 Phone: 714 668 3660
 Fax: 714 668 1107
 sales@allscape.net
 http://www.allighting.com

BL-125/126/127

Product Order Guide

Series	Max Watts	Lamp Type	Voltage ¹	Finish ¹	Options
BL-125	18 CFQ	CFQ ²	120	BK Black	P ³ Specify Pendant Length
BL-126	70 MH	T6	208	BZ Bronze	SPT Nema 1 (E-17 & T6)
	70 MH	PAR38	240	WH White	FLD Nema 3 (E-17 & T6)
	70 MH	E-17	277	GR Green	RB Remote Ballast
	70 HPS	E-17		NA Natural Aluminum	
	42 CFT	CFT ²		GY Gray	
				CC Custom Color	
BL-127	18 CFQ	CFQ ²			D Downlight
	70MH	PAR38			UD Up/Downlight
	70MH	E-17			U Uplight
	70HPS	E-17			SPT Nema 1 (E-17 & T6)
	42CFT	CFT ²			FLD Nema 3 (E-17 & T6)
	70 MH	T6			RB Remote Ballast


1 Consult factory for other colors and voltages

2 CF = single biax, CFQ = double biax, CFT = triple biax


3 BL-125 only

Example: BL-125-13CF-120-BK-P30"

Photometric Data




BL-125-13CFQ
 860 Lumens
 8.0 ft Mounting Height
 ISOLUX Curves - value in initial footcandles




BL-126-50MV
 2,000 Lumens
 8.0 ft Mounting Height
 ISOLUX Curves - value in initial footcandles

Luminaire Dimensions


Luminaire	A		B		C		D		E		Weight	
	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	lbs.	kg
BL-125	8.00	203	12.40	315	71.01	1805					6.2	2.8
BL-126	8.00	203	12.40	315							10.6	4.8
BL-127-D	8.00	203	12.01	305					11.42	290	11.5	5.2
BL-127-UD	8.00	203					20.50	508	11.50	292	20.0	9.0




BL-125



BL-126



BL-127-D



BL-127-UD