

- Walkways**
- Building Entrances**
- Parking Lots**
- Shopping Malls**



### Specifications



**Certifications** The fixture shall be ETL and CETL listed for wet location.

**Sphere** The single piece seamless acrylic or polycarbonate spheres (16", 18", 20", 22") shall be sealed to casting with neoprene gasketing and retained by a heavy-gauge aluminum clamp. Opal, clear and bronze globes are available in either acrylic or polycarbonate. The fixture shall be ETL listed "suitable for wet locations."

**Optical System** Opal acrylic (BO) spheres are standard. Clear and bronze tints are available with standard refractors.

**Installation** Field installation to bracket or pole shall be accomplished without having to remove or disassemble any fixture components. The standard unit shall slipfit a 3" round pole or can be supplied with a cast aluminum fitter, with integral tenon which shall internally fit 4" round aluminum poles or 3.5" round stems. Other sizes shall be available upon request.

**Ballast** Ballasts shall be post-line (where available) or core and coil mounted in head. All CWA ballasts (+10% dto -10% lamp power regulation) are rated for -20 degree F operation. All non-CWA ballasts shall be HPF ballasts. The fixture shall be factory pre-wired, completely assembled and electronically tested prior to shipment. Quick-disconnects are standard.

**Finish** BK-BZ-WH-GR-GY-NA baked enamel standard, other colors available.

PROJECT
FIXTURE TYPE
CATALOG#

2930 South Fairview Street  
 Santa Ana, CA 92704  
 Phone: 714 668 3660  
 Fax: 714 668 1107  
 allighting@earthlink.net  
 http://www.allighting.com

# AA-02

## Product Order Guide

Series	Head Size	Number Fixtures	Max Watts	Lamp Type	Voltage <sup>1</sup>	Optics	Finish <sup>1</sup>	Options
AA-02	16 <sup>3</sup>	1	175 MH	E-17 <sup>2</sup>	120	BO	BZ Bronze	F Fusing
	18	1T	250 MH	ED-28	208	BOP	BK Black	FF Double Fusing
	20	BCT	150 HPS	E-17 <sup>2</sup>	240	BC	WH White	
	22	WBT			277	BCR	GR Green	
		2T				BS	NA Natural Aluminum	
		3TT				BSR	GY Gray	
		3YT					CC Custom Color	
		4T						
		5T						

<sup>1</sup> Consult factory for other colors and voltages

<sup>2</sup> Lamps 175 W and below are medium base.

<sup>3</sup> 16" fixture uses PostLine ballast where available.

## Example: AA-02-22-5T-150HPS-E17-120-BCR-BK

### Optics

BO	Opal Acrylic
BOP	Opal Polycarbonate
BC	Clear Acrylic
BCR	Clear Acrylic with Refractor
BS	Bronze Acrylic
BSR	Bronze Acrylic with Refractor

### Number of Fixtures

1	Single to Slipfit 3" OD Pole Top
1T	Single with Stem Tenon
BCT	Single Arm Mount with StemTenon
WBT	Single Wall Mount with StemTenon
2T	Double Arm Mount at 180 with StemTenon
3TT	Triple Arm Mount at 90 with StemTenon
3YT	Triple Arm Mount at 120 with StemTenon
4T	Quad Arm Mount at 90 with StemTenon
5T	Penta Arm Mount with StemTenon

See Installation Instructions for Stem Tenon Details.

### Luminaire Parameters

Luminaire	Weight	EPA	INC Max Wattage	HPS Max Wattage	MH Max Wattage
AA-02-16	40#	0.8	100	100	100
AA-02-18	44#	1.06	175	150	175
AA-02-20	50#	1.32	250	150	175
AA-02-22	62#	1.58	250	150	250