

- Walkways**
- Building Entrances**
- Parking Lots**
- Shopping Malls**



Specifications



Certifications The fixture shall be ETL and CETL listed for wet location.

Cubes The single piece seamless acrylic or polycarbonate cubes (14", 16", 18") with sharp or rounded corners shall be sealed to castings with neoprene gasketing and retained by a heavy gauge aluminum clamp. The fixture shall be ETL listed "suitable for wet locations." Opal, clear and bronze cubes shall be available in either acrylic or polycarbonate.

Optical System Opal acrylic (CO) cubes are standard. Clear and bronze tints are available with standard refractors.

Installation Field installation to bracket or pole shall be accomplished without having to remove or disassemble any fixture components. The standard unit shall slipfit a 3" round pole or can be supplied with a cast aluminum fitter, with integral tenon which shall internally fit 4" round aluminum poles or 3.5" round stems. Other sizes shall be available upon request.

Ballast Ballasts shall be post-line where available or core and coil mounted in head. All CWA ballasts (+10% to -10% lamp power regulation) are rated for -20 degree F operation. All non-CWA ballasts shall be HPF ballasts. The fixture shall be factory pre-wired, completely assembled and electronically tested prior to shipment. Quick-disconnects are standard.

Finish BK-BZ-WH-GR-GY-NA baked enamel standard, other colors available.

| |
|---------------------|
| PROJECT |
| FIXTURE TYPE |
| CATALOG# |

2930 South Fairview Street
 Santa Ana, CA 92704
 Phone: 714 668 3660
 Fax: 714 668 1107
 allighting@earthlink.net
 http://www.allighting.com

AA-03

Product Order Guide

| Series | Head Size | Number Fixtures | Max Watts | Lamp Type | Voltage ¹ | Optics | Finish ¹ | Options |
|--------|-----------------|-----------------|-----------|-------------------|----------------------|--------|---------------------|------------------|
| AA-03 | 14 ³ | 1 | 175 MH | E-17 ² | 120 | CO | BZ Bronze | F Fusing |
| | 16 ³ | 1T | 250 MH | ED-28 | 208 | CC | BK Black | FF Double Fusing |
| | 18 | BCT | 175 HPS | E-17 ² | 240 | CCR | WH White | |
| | | WBT | 250 HPS | ED-18 | 277 | CB | GR Green | |
| | | 2T | | | | CBR | NA Natural Aluminum | |
| | | 3TT | | | | | GY Gray | |
| | | 3YT | | | | | CC Custom Color | |
| 4T | | | | | | | | |
| 5T | | | | | | | | |

1 Consult factory for other colors and voltages

2 Lamps 175 W and below are medium base.

3 14" & 16" fixture uses PostLine ballast where available.

Example: AA-03-16-3YT-100HPS-E17-120-CO-BK

Optics

| | |
|-----|-------------------------------|
| CO | Opal Acrylic |
| CC | Clear Acrylic |
| CCR | Clear Acrylic with Refractor |
| CB | Bronze Acrylic |
| CBR | Bronze Acrylic with Refractor |

Number of Fixtures

| | |
|-----|--|
| 1 | Single to Slipfit 3" OD Pole Top |
| 1T | Single with Stem Tenon |
| BCT | Single Arm Mount with StemTenon |
| WBT | Single Wall Mount with StemTenon |
| 2T | Double Arm Mount at 180 with StemTenon |
| 3TT | Triple Arm Mount at 90 with StemTenon |
| 3YT | Triple Arm Mount at 120 with StemTenon |
| 4T | Quad Arm Mount at 90 with StemTenon |
| 5T | Penta Arm Mount with Stem3Tenon |

See Installation Instructions for Stem Tenon Details.

Luminaire Parameters

| Luminaire | Weight | EPA | INC Max Wattage | HPS Max Wattage | MH Max Wattage |
|-----------|--------|-----|-----------------|-----------------|----------------|
| AA-03-14 | 40# | 1.4 | 150 | 70 | N/A |
| AA-03-16 | 42# | 1.8 | 200 | 150 | 100 |
| AA-03-18 | 46# | 2.3 | 250 | 150 | 175 |