

DIGIT TILE:

Style Code	DGT
Specifications	
Construction	Tip-Sheared Patterned Scroll
Yarn Content	Avalar® RE Nylon
Odor Reducer	Puralex®
Dye Method	Solution
Machine Gauge	1/12 in. (47.2 col./10 cm.)
Stitch Count	10 S.P.I. (39.4/10 cm.)
Finished Pile Thickness	.146 in. (3.71 mm.)
Average Density	5,918
Yarn Weight Tufted	24 oz./yd.2 (813 g./m2)
Primary Backing	Non Woven
Secondary Backing	Nexterra®
Total Recycled Content	40% Minimum Post consumer Recycled Content based on Total Weight of Product
Modular Tile Width	24" x 24" (61 cm. x 61 cm.)
Performance	
Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1(ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP8595
Warranties	
Wear	Lifetime Limited Warranty
Static	Lifetime Warranty
Edge Ravel	Lifetime Warranty
Delamination	Lifetime Warranty, under normal use
Tuft Bind	Lifetime Warranty
Stain	Lifetime Limited Warranty
Additional Information	
Custom Colors	iDesignCarpet.com
Backing Options	See iLoc® backings at www.bolyu.com
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



BÖLYÜ

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075