

FLASH TILE:

Style Code

FSH

Specifications

Construction	Patterned Loop
Yarn Content	Avalar® RE Nylon
Odor Reduction	Puralex®
Dye Method	Solution
Machine Gauge	1/12 in. (47.2 col./10 cm.)
Stitch Count	13.3 S.P.I. (52.3/10 cm.)
Finished Pile Thickness	.162 in. (4.11 mm)
Average Density	7,111
Yarn Weight Tufted	32 oz./yd.2 (1,084 g./m2)
Primary Backing	Non Woven
Secondary Backing	Nexterra
Total Recycled Content	40% Minimum Post consumer Recycled Content based on Total Weight of Product
Modular Tile Width	24" x 24" (61 cm. x 61 cm.)

Performance

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1(ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP8595

Warranties

Wear	Lifetime Limited Warranty
Static	Lifetime Warranty
Edge Ravel	Lifetime Warranty
Delamination	Lifetime Warranty, under normal use
Tuft Bind	Lifetime Warranty
Stain	Lifetime Limited Warranty

Additional Information

Custom Colors	iDesignCarpet.com
Backing Options	See iLoc® backings at www.bolyu.com
Samples	800 451 1250
Recommended Installation	Quarter Turned, Monolithic, Ashlar Vertical, Ashlar Brick

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



BÖLYÜ

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075