

INFINITY TILE:

Style Code

6TINF

Specifications

Construction	Patterned Scroll
Yarn Content	Avalar® RE Nylon
Odor Reduction	Puralox®
Dye Method	Solution
Machine Gauge	1/12 in (47.2 in./10 cm.)
Stitch Count	10 S.P.I (39.4/ 10 cm.)
Finished Pile Thickness	.110 in. (2.79 mm.)
Average Density	6,545
Yarn Weight Tufted	20 oz. /yd. ² (678 g./m. ²)
Primary Backing	Nonwoven
Secondary Backing	Nexterra®
Total Recycled Content	Manufactured with 40% Pre-Consumer Recycled Content
Modular Tile Width	24" x 24" (61 cm. x 61cm.)

Performance

Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification # GLP8595

Warranties

Wear	Lifetime Limited Warranty
Static	Lifetime Warranty
Tuft Bind	Lifetime Warranty
Edge Ravel	Lifetime Warranty
Zippering	Lifetime Warranty, not to zipper wet or dry
Pilling & Fuzzing	Lifetime Warranty
Delamination	Lifetime Warranty, under normal use
Dimensional Stability	Lifetime Warranty

Additional Information

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.bolyu.com
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



BÖLYÜ

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075