

KEYSTONE:

Style Code	6KEY
Specifications	
Construction	Textured Loop Pattern
Yarn Content	Avalar® RE Nylon
Odor Reduction	Puralex®
Dye Method	Solution
Machine Gauge	1/10 in (39.4 in./10 cm.)
Stitch Count	10 S.P.I (39.4/ 10 cm.)
Finished Pile Thickness	.172 in. (4.37 mm)
Average Density	4,688
Yarn Weight Tufted	22 oz. /yd. ² (746 g./m. ²)
Primary Backing	Masterline® Woven Primary
Secondary Backing	Woven Polypropylene
Total Recycled Content	Manufactured with 25% Pre-Consumer Recycled Content
Pattern Repeat	.50" w x .80" l (1.3 cm. x 2.0 cm.)
Performance	
Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP7078
Warranties	
Wear	10 Year Limited Warranty
Static	Lifetime Warranty
Stain	Lifetime Warranty
Colorfastness	Lifetime Warranty Against Light & Atmospheric Contaminants
Additional Information	
Custom Colors	Contact Sales Representative
Coordinating Styles	Multiple
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075

BÖLYÜ