

SPECIFICATIONS

Construction	Textured Loop Pattern
Yarn Content	Cambridge SD Nylon
Yarn Recycled Content	Manufactured with 25% Pre-Consumer Recycled Content
Dye Method	Solution
Machine Gauge	1/10 in (39.4 in./10cm)
Stitch Count	13 S.P.I (51.2/ 10cm)
Finished Pile Thickness	.080 in. (2.03 mm)
Average Density	9,000
Yarn Weight Tufted	20 oz. /yd. ² (678 g/m ²)
Primary Backing	Non Woven
Secondary Backing	Nexterra® with 85% Post Consumer Content and Puralex®
Width	24" x 24" (61 cm. x 61 cm.)

PERFORMANCE

Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label	Certification # GLP8595

WARRANTIES

Wear	Lifetime Limited Warranty
Static	Lifetime Warranty
Tuft Bind	Lifetime Warranty
Edge Ravel	Lifetime Warranty
Zippering	Lifetime Warranty, not to zipper wet or dry
Pilling & Fuzzing	Lifetime Warranty
Delamination	Lifetime Warranty, under normal use
Dimensional Stability	Lifetime Warranty

ADDITIONAL INFORMATION

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.cambridgecarpet.com
Additives	Puralex® is a refresher that is environmentally friendly and specially formulated to help purify the air.
Samples	800 451 1250



Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.

LEGEND

style # 6TLEG

Cambridge®

201 Princeton Boulevard
P.O. Box 1110
Adairsville, GA 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada JOH 1A0
888 467 5075

www.cambridgecarpet.com

A Beaulieu Commercial Brand