

AMALFI

Wall mounted indirect reflector luminaire is suitable for both interior and exterior applications. Luminaire is precision-machined from billet aluminum, then satin anodized. Domed lens is temperature- resistant borosilicate glass. Spun anodized reflector, precision- formed support struts and inverted tapered mounting arm form clean angular lines. Cast aluminum housing is finished in finely textured paint to create a unique appearance. All hardware is stainless steel.

AMALFI G

Same as AMALFI, except with 12° tilted bracket. Standard color; matte silver grey metallic. Special colors available.



Wet Location

Model	Mounting	Lamp
AM670	Wall	50 Low Voltage Halogen / 20 Low Voltage Halogen
AM670G	Wall	50 Low Voltage Halogen / 20 Low Voltage Halogen

Additional information:

Drawings

Downloads

[AM670g.swf](#)

Catalogue page

Downloads

[Hessamerica_AMALFI_wml.pdf](#)

Photometric reports

Downloads

[AM670/AM900_-_MR16.ies](#)

3D data

Downloads

[3D_Amalfi_WL.zip](#)

Specification sheets

Downloads

[AMALFI 670G Wall Mounted Luminaire](#)

[AMALFI 670 Wall Mounted Luminaire](#)

Product brief

Corresponding products



Illuminating Bollards
[AMALFI](#)



Pole Mounted Luminaires
[AMALFI](#)

