

LEDIA LL OD

Elegant in any context, LEDIA LL OD is ideally suited to a variety of recessed inground applications. It is available in four lengths. Frameless glass lens integrates subtly into pavers or concrete walkways to highlight or act as directional identifiers. The tempered glass lens, coated internally with a translucent white coating, is bonded to the stainless steel housing providing a sealed enclosure. LEDIA mounts into a recessed stainless steel subframe, which serves as a cable vault for making power connections. Remote 120vAC/10vDC power supply unit is required. LED colors; red, blue, green, amber, white. Contact factory for in-wall applications.



Listed 1838, Low Voltage Landscape Lighting Systems

Model	Dimensions	Qty LEDs	Wattage
LEDIA LL-OD-09	9.5" x 1.1"	16 LEDs	2
LEDIA LL-OD-18	18.1" x 1.1"	32 LEDs	4
LEDIA LL-OD-27	27.2" x 1.1"	48 LEDs	6
LEDIA LL-OD-36	35.8" x 1.1"	64 LEDs	8

Additional information:

Drawings

Downloads

[LL-OD-09.swf](#)

[LL-OD-18.swf](#)

[LL-OD-27.swf](#)

[LL-OD-36.swf](#)

Catalogue page

Downloads

[Hessamerica_LEDIA_LL.pdf](#)

Photometric reports

Downloads

[LEDIA_LL_240_>_LED.ies](#)

[LEDIA_LL_460_>_LED.ies](#)

[LEDIA_LL_690_>_LED.ies](#)

[LEDIA_LL_910_>_LED.ies](#)

Specification sheets

Downloads

[LEDIA LL OD 09 LED Illuminating Strip](#)

[LEDIA LL OD 18 LED Illuminating Strip](#)

[LEDIA LL OD 27 LED Illuminating Strip](#)

[LEDIA LL OD 36 LED Illuminating Strip](#)

Product brief

References

