


NOVARA 4500 ML

Cast aluminum and stainless steel create a synthesis of form and function in the Novara. The angular heavy cast aluminum housing is punctuated by distinctive cooling fins. Doorframe and mounting knobs are constructed of polished high-grade stainless steel. Luminaire mounting bracket is brushed stainless steel. Single or twin configurations may be fitted with a clear, etched, or optional prismatic lens. Electrical conductor is housed in attractive braided stainless steel line. Canopy and stem are satin anodized aluminum. All hardware is stainless steel. Standard color; matte silver grey metallic. Special colors available.



Model	Mounting	Lamp
NV450ML-X	Pendant	70 MH / 42 CFL / 200 Halogen



Additional information:

Drawings

Downloads

[NV450ML-X.swf](#)

Catalogue page

Downloads

[Hessamerica_NOVARA_ML_penl.pdf](#)

Photometric reports

Downloads

[NV450ML.ies](#)

[NV450ML_|_42w_CFL.ies](#)

Specification sheets

Downloads

[NOVARA 4500 ML CFL Pendant Luminaire](#)

[NOVARA 4500 ML Halogen Pendant Luminaire](#)

[NOVARA 4500 ML HID Pendant Luminaire](#)

Product brief

Corresponding products



Illuminating Bollards
[NOVARA](#)



Pendant Luminaires
[NOVARA L](#)



Pendant Luminaires
NOVARA ML



Pole Mounted Luminaires
NOVARA ML



Pole Mounted Luminaires
NOVARA Q



Pole Mounted Luminaires
NOVARA S



Pole Mounted Luminaires
NOVARA SAL



Pole Mounted Luminaires
NOVARA SL



Pole Mounted Luminaires
NOVARA SXL



Wall Mounted Luminaires
NOVARA



Wall Mounted Luminaires
NOVARA ML



Wall Mounted Luminaires
NOVARA Q



Wall Mounted Luminaires
NOVARA S



Wall Mounted Luminaires
NOVARA SL

