White 010

Paradise 2659

Specifications

Contents

100% recycled polyester

Weight

 9.5 ± 0.5 oz./lin. yd.

Width

66" min. useable

Cleaning Code

W-S

Performance









Breaking Strength (ASTM D5034)

225 lbf min. warp and 125 lbf min fill

Tear (ASTM D2261)

min. warp and fill

Colorfastness to light (AATCC 16 Option 3)

Grade 4 min. at 40 hours

Colorfastness to crocking (AATCC 8)

Grade 4 min. dry & Grade 3 min. wet

Flammability

ASTM E84 - Class I or A NFPA 701 TM#2 flat sheets - Pass (printed fabric only)

NRC of anechoic termination

1.00

NRC of fabric in front of anechoic termination

.90



Terratex is a registered trademark of True Textiles, Inc. and designates fabrics that are made from 100% recycled or compostable material using increasingly sustainable manufacturing practices to produce a high quality product that is recyclable at the end of its useful life. (terratex.com)



CO² emissions from 100% of the electricity used by the manufacturer to produce this product have been measured and offset in accordance with the CarbonNeutral Protocol.

The plot below summarizes impedance tube measurements of absorption of an anechoic termination and various fabrics in front of the anechoic termination.

Acoustical Performance for Panel Applications



