

Kelly 1751

Casablanca 34054

Specifications

Contents

100% recycled polyester

Weight

11.3 ± 0.5 oz./lin. yd.

Width

54" min. useable

Repeat

6.75" vertical, 6.75" horizontal

Treatment

BLOCKaide™

Backing

s.b.r. latex



Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Performance



Breaking Strength (ASTM D5034)

125 lbf min. warp and 150 lbf min fill

Tear (ASTM D2261)

10 lbf min. warp and fill

Seam Slippage (ASTM D4034)

60 lbf min. warp and fill

Pilling resistance (ASTM D3511)

Class 4 min.

Colorfastness to light (AATCC 16 Option 3)

Grade 4 min. at 40 hours

Colorfastness to crocking (AATCC 8)

Grade 4 min. dry & Grade 3 min. wet

Colorfastness to water (AATCC 107)

Grade 4 min. color change & Grade 3 min. staining

Wyzenbeek Abrasion resistance (ASTM D4157)

30,000 double rubs min. cotton duck

Flammability

CA Tech Bulletin 117 Sec. E

NFPA 260/UFAC Fabric Classification - Class I