

Eclipse™ *ClimaPlus*™ Illusion™ and Pedestals™



10

Year Availability
78785

HRC

High Recycled Content



ECLIPSE PEDESTALS IV Panels with *CLIMAPlus* Superior Performance/
DONN CENTRICITEE DXT Suspension System

LEED Credits

Recycled Content: 77%
CLIMAPlus Superior Performance for Mold and Mildew

MR				EQ		
Waste Reduction ¹	Recycled Content	Regional Materials ²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

Features and Benefits

- A variety of face scores create the illusion of a smaller-scaled ceiling system without compromising accessibility
- Solid NRC performance of up to .70 meets general office acoustical needs for sound absorption
- *CLIMAPlus* 30-year lifetime system warranty to withstand temperature and humidity conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a *DONN*® brand suspension system

Applications

- Boutiques
- Schools
- Reception lobbies
- Transportation terminals

Substrate

- X-Technology mineral fiber



Fine-textured panel

To order samples, go to usg.com



White

Eclipse™ *ClimaPlus™* Illusion™ and Pedestals™

To order samples/literature:
 – Web: usg.com
 – E-mail: samplit@usg.com
 – Fax: 888.874.2348
 Technical Services: 800.USG.4YOU

Web Sites: usg.com
usgdesignstudio.com
sustainableceilings.com
seismicceilings.com

See usg.com for
 the most up-to-date
 product information.

30 Year System Warranty – No visible sag – Mold/mildew protection	UL Classified													
	Edge	Panel Size	Class	Item No.	NRC	CAC Min. ³	LR ⁴	Color	Grid Options	VOC ⁵ Emissions	Anti-Mold & Mildew	Recycled Content ²	Panel Cost	
ECLIPSE CLIMAPlus ILLUSION Two/24 Panels The look of 2'x2' panels	SLT ⁵ 	2'x4'x3/4"	Class A	78785	.70 	35	.84	White	A	Low		77% 	\$	
	ILT ⁶ 	2'x4'x3/4"	Class A	78085	.70 	35	.84	White	B, C	Low		77% 	\$	
ECLIPSE CLIMAPlus ILLUSION Four/48 Panels The look of 48"x6" linear strips	SLT ⁶ 	2'x4'x3/4"	Class A	78711 ⁸	.70 	35	.84	White	A	Low		77% 	\$	
	ILT ⁷ 	2'x4'x3/4"	Class A	78011 ⁸	.70 	35	.84	White	B, C	Low		77% 	\$	
ECLIPSE CLIMAPlus PEDESTALS I Panels Triple-step scoring	PE/SLT 	2'x2'x3/4"	Class A	72715	.65 	35	.84	White	D	Low		77% 	\$	
	PE/ILT 	2'x2'x3/4"	Class A	72015	.65 	35	.84	White	E, F	Low		77% 	\$	
ECLIPSE CLIMAPlus PEDESTALS IV Panels Triple-step scoring in 12"x12" modules	PE/SLT ⁵ 	2'x2'x3/4"	Class A	72716	.65 	35	.84	White	D	Low		77% 	\$	
	PE/ILT ⁶ 	2'x2'x3/4"	Class A	72215	.65 	35	.84	White	E, F	Low		77% 	\$	
	Illusion Two/24		Illusion Four/48		Pedestals I		Pedestals IV							
Patterns														
Legend														
Low Emissions (VOC Class) Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.					CLIMAPlus Superior Performance⁷ Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold and mildew.					High Recycled Content Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.				
	A DX®/DXL™	B CENTRICITEE™ DXT	C DXI™	D DX/DXL	E CENTRICITEE DXT	F IDENTITEE™ DXI™								
Grid Profile Options														

Physical Data/ Footnotes

Product literature
 Data sheet: SC1846B

ASTM E1264 classification
 Type III, Form 1, Pattern EIK (Illusion) or Pattern EI (Pedestals)

ASTM E84 surface burning characteristics
 Class A
 Flame spread: 25
 Smoke developed: 50

Weight
 .97-1.2 lb./sq. ft.

Thermal resistance
 R-2.0

Maximum backloading
 See Warranty for details.

Maintenance
 Can be cleaned easily with a soft brush or vacuum.

Proprietary technology
 This product's unique combination of sag resistance and sound performance results from a proprietary technology.

Footnotes

1. Applies when USG acoustical ceilings recycling program is utilized.
2. For details, see LEED report generator at usgdesignstudio.com.
3. Adding sound masking can be as effective as using a ceiling panel with a higher CAC rating, providing increased privacy between enclosed office spaces.
4. LR values are shown as averages.
5. Panels have a 15/16" routing.
6. Panels have a 9/16" routing.

7. Panel face and back surfaces treated with a proprietary, broad-spectrum anti-microbial standard formulation that inhibits and retards the growth of mold/mildew. For details, see *Ceiling Systems Warranties and Limitations* (SC2102) and *CLIMAPlus Ceilings Certification of Performance* (SC2451)
8. 5,000 sq. ft. minimum.
9. No formaldehyde is added to any ingredient or during the manufacturing process for all mineral fiber acoustical ceiling products manufactured by USG Interiors, LLC.

Note
 Panels with face routing do not carry USG's *CLIMAPlus* non-sag warranty. Refer to standard commercial ceilings warranty.



Manufactured by USG Interiors, LLC.
 550 West Adams Street
 Chicago, IL 60661

The following are trademarks of USG Interiors, LLC, or a related company: CENTRICITEE, CLIMAPlus, DOWN, DX, DXI, DXL, DXT, ECLIPSE, IDENTITEE, ILLUSION, PEDESTALS, USG.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC1846/rev. 1-12
 © 2012 USG Interiors, LLC.
 Printed in U.S.A.