



Halcyon™ *ClimaPlus*™ Planks and Large Sizes



HALCYON Planks with *CLIMAPLUS* Performance/
DONN CENTRICITEE DXT Suspension System

LEED Credits

Recycled Content: 40% – 41%
LEED Recycled Content Contribution: 40% – 41%
CLIMAPLUS No-Sag Warranty

MR				EQ		
Waste Reduction	Recycled Content	Regional Materials¹	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
	●	●			●	●

Features and Benefits

- Exceptional noise reduction with NRC values up to 1.00 for open-plan offices
- High light-reflective finish (LR-.88) reduces light fixtures and energy use
- Washable and Scrubbable finish – Impact and Scratch Resistant
- Coordinates visually with MARS for open/closed plan applications
- Compatible with the LOGIX integrated ceiling system
- Non-directional, monolithic visual reduces installation time and waste
- *CLIMAPLUS*™ 30-year lifetime system warranty against visible sag, mold and mildew

Applications

- Open-plan areas
- Areas with indirect lighting
- Corridors⁶
- Convention halls and concourses
- Reception and lobby areas⁶
- Libraries

Substrate

- Fiberglass

Call 888.874.2450 for samples



White

Fine-textured panel

Halcyon™ ClimaPlus™

Planks and Large Sizes

To order samples/literature:
 – Web: usg.com
 – E-mail: samplit@usg.com
 – Fax: 847.232.1594
 Technical Services: 800.USG.4YOU

Web Sites: usg.com
usgdesignstudio.com
sustainableceilings.com
seismicceilings.com

See usg.com for
 the most up-to-date
 product information.

30

Year System Warranty
 – No visible sag
 – Mold/mildew protection

HALCYON
 ClimaPlus
 Planks

UL Classified												
Edge	Panel Size ^{2,3}	Class	Item No.	NRC	CAC Min.	LR ⁴	Color	Grid Options	Anti-Mold & Mildew	Recycled Content ¹	Panel Cost	
												
SQ 	2'x6'x3/4"	Class A	97262	.90		20	.88 	White	A, B	40%	\$\$\$	
	2'x8'x3/4"	Class A	97263	.90		20	.88 	White	A, B	40%	\$\$\$	
SL 	2'x6'x1"	Class A	99268	.95		20	.88 	White	D	41%	\$\$\$	
	2'x8'x1"	Class A	99269	.95		20	.88 	White	D	41%	\$\$\$	
FL 	2'x6'x1"	Class A	98348	.95		20	.88 	White	E, F, G, H	41%	\$\$\$	
	2'x8'x1"	Class A	98197	.95		20	.88 	White	E, F, G, H	41%	\$\$\$	
SQ 	4'x4'x1"	Class A	98441	.95		20	.88 	White	A, B	41%	\$\$\$	
	4'x8'x1"	Class A	98481	.95		20	.88 	White	A, B	41%	\$\$\$	
SL 	4'x4'x1"	Class A	98443	.95		20	.88 	White	D	41%	\$\$\$	
FL 	4'x4'x1"	Class A	98445	.95		20	.88 	White	E, F, G, H	41%	\$\$\$	

Legend

ClimaPlus Inherent Performance⁵


Fiberglass substrate is inherently resistant to the growth of mold and mildew.

A DX®/DXL™	B DXW™	C CENTRICITEE™ DXT	D DX/DXL	E CENTRICITEE™ DXT	F FINELINE® DXF	G FINELINE® 1/8 DXFF	H IDENTITEE™ DXI™

Grid Profile Options

Stabilizer Bars³

Use to stabilize grid installation without cross tees



SB12	18" Stabilizer Bar
SB24	2' Stabilizer Bar
SB36	3' Stabilizer Bar
SB48	4' Stabilizer Bar
SB48-24	4' Stabilizer Bar notched 2' on center
SB60	5' Stabilizer Bar
CC15-4-2	4' Stabilizer Bar notched 2' on center

Physical Data/ Footnotes

Product literature

Data sheet: SC2483

ASTM E1264 classification

Type XII, Form 2, Pattern E & G

ASTM E84 surface burning characteristics

Class A

Flame spread: 25

Smoke developed: 50

Weight

0.38 lb./sq. ft. (3/4" panels)

0.47 lb./sq. ft. (1" panels)

Thermal resistance

R-3.3 (3/4" panels)

R-4.4 (1" panels)

Maximum backloading

See Warranty for details.

Maintenance

Can be cleaned easily with a soft brush or vacuum.

Scrubbability

Exceeds 1000+ scrub cycles without surface break or the extent of abrasion (ASTM D2486)

Washability

Exceeds 1000+ wash cycles without surface break or the extent of abrasion (ASTM D4828)

Footnotes

1. For details, see LEED report generator at usgdesignstudio.com.

2. Custom-size panels available.

Please contact your USG sales representative for details.

3. Stabilizer bars recommended for panels 5' and longer. See USG parts list IC532 for details.

4. LR values are shown as averages.

5. For details, see *Ceiling Systems Warranties and Limitations* (SC2102) and *ClimaPlus Ceilings Certification of Performance* (SC2451).

6. For wall-to-deck applications.



Manufactured by USG Interiors, Inc.
 550 West Adams Street
 Chicago, IL 60661

The following are trademarks of USG Interiors, Inc. or a related company: ClimaPlus, Down, DX, DXF, DXI, DXL, DXT, DXW, Halcyon, Identitee, USG.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC2483/rev. 10-11
 © 2011, USG Interiors, Inc.
 Printed in U.S.A.