



MILLENNIA Panels with *CLIMAPLUS* Superior Performance/
DONN DX/DXL Suspension System

LEED Credits

Recycled Content: 75%

CLIMAPLUS Superior Performance for Mold and Mildew

MR				EQ		
Waste Reduction ¹	Recycled Content	Regional Materials ²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

Features and Benefits

- Market's fastest-installing fine-textured ceiling is an economical alternative to face-laminated panels
- NRC meets general office acoustical needs for sound absorption
- *CLIMAPLUS*™ 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/ 95% relative humidity without visible sag when used with a *DONN*® brand suspension system

Applications

- Retail stores
- Hospitality
- Office and conference areas
- Transportation terminals

Substrate

- X-Technology mineral fiber



Fine-textured panel

To order samples, go to usg.com



UL Classified													
Edge	Panel Size	Class	Item No.	NRC	CAC Min. ³	LR ⁴	Color	Grid Options	VOC ¹⁰ Emissions	Anti-Mold & Mildew	Recycled Content ²	Panel Cost	
MILLENNIA CLIMAPlus Panels	SQ	2'x2'x3/4"	Class A	76505	.70	.85	White	A, B, C	Low		75% HRC	\$\$	
		2'x4'x3/4"	Class A	78505	.70	.85	White	A, B	Low		75% HRC	\$\$	
	SLT	2'x2'x3/4"	Class A	76705	.70	.85	White	D	Low		75% HRC	\$\$	
		2'x4'x3/4"	Class A	78705	.70	.85	White	D	Low		75% HRC	\$\$	
	FLB	2'x2'x3/4"	Class A	76907	.70	.85	White	E, F, G, H	Low		75% HRC	\$\$	
		2'x4'x3/4"	Class A	76901	.70	.85	White	E, F, G, H	Low		75% HRC	\$\$	
MILLENNIA CLIMAPlus Tile ^{5,6}	BESK	12"x12"x3/4"	Class A	70003	.60	.85	White	I	Low		75% HRC	\$\$\$\$	
MILLENNIA CLIMAPlus Illusion Two/24 Panels The look of 2'x2' panels	SLT ⁷	2'x4'x3/4"	Class A	78780	.70	.85	White	D	Low		75% HRC	\$\$	
	ILT ⁸	2'x4'x3/4"	Class A	78080	.70	.85	White	J, K	Low		75% HRC	\$\$	
Illusion Two/24													
Patterns													
Legend													
<div><div>Low Emissions (VOC Class) Classified as low-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.</div><div>CLIMAPlus Superior Performance¹⁰ Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold and mildew.</div><div>HRC High Recycled Content Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.</div></div>													
	A DX®/DXL™	B DXW™	C CENTRICITEE™ DXT	D DX/DXL	E CENTRICITEE DXT	F FINELINE® DXF	G FINELINE® 1/8 DXFF	H IDENTITEE™ DXI™	I DX®/DXL™ Concealed	J CENTRICITEE DXT	K IDENTITEE DXI		
Grid Profile Options													

Physical Data/ Footnotes

Product literature
 Data sheet: SC1824
ASTM E1264 classification
 Type III, Form 1, Pattern E, G
ASTM E84 surface burning characteristics
 Class A
 Flame spread: 25
 Smoke developed: 50
Weight
 1.02-1.05 lb./sq. ft. (panels and tile)

Thermal resistance
 R-2.0
Maximum backloading
 See Warranty for details.
Maintenance
 Can be cleaned easily with a soft brush or vacuum.
Proprietary technology
 This product's unique combination of sag resistance and sound performance results from a proprietary technology.

Footnotes
 1. Applies when USG acoustical ceilings recycling program is utilized.
 2. For details, see LEED report generator at usgdesignstudio.com
 3. Adding sound masking can be as effective as using a ceiling panel with a higher CAC rating, providing increased privacy between enclosed office spaces.
 4. LR values are shown as averages.
 5. Contact USG for adhesive recommendations for 12"x12" glue-up applications.
 6. Not UL Classified for acoustics.
 7. Panels have a 15/16" routing.

8. Panels have a 9/16" routing.
 9. Panel face and back surfaces treated with a proprietary, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold and mildew. For details, see *Ceiling Systems Limited Warranty Commercial Applications* (SC2102) and *CLIMAPlus Ceilings Certification of Performance* (SC2451).
 10. No formaldehyde is added to any ingredient or during the manufacturing process for all mineral fiber acoustical ceiling products manufactured by USG Interiors, LLC.



Manufactured by USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

The following are trademarks of USG Interiors, LLC or a related company: CENTRICITEE, CLIMAPlus, DOWN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, IDENTITEE, MILLENNIA, USG.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC1824/rev. 1-12
 © 2012 USG Interiors, LLC
 Printed in U.S.A.