

Radar™ *ClimaPlus*™ Open Plan



High Recycled Content



RADAR Open Plan with *CLIMAPLUS* Superior Performance/
DONN DX/DXL Suspension System

See LEED report tool at usgdesignstudio.com
for detailed sustainability information.

Features and Benefits

- Non-directional all-purpose ceiling pattern
- .75 NRC for increased sound control in open-plan areas
- *CLIMAPLUS*™ 30-year lifetime system warranty to withstand conditions up to 104°F (40°C)/95% relative humidity without visible sag when used with a *DONN*® brand suspension system
- High-NRC – Formulation helps comply with ANSI S 12.60 classroom guidelines

Applications

- Open office plans
- Classrooms
- Conference rooms
- Privacy rooms

Substrate

- Water-felted mineral fiber



Lightly-textured panel

To order samples, go to usg.com



White

Radar™ *ClimaPlus*™ Open Plan

To order samples/literature:
 – Web: usg.com
 – E-mail: samplit@usg.com
 – Fax: 888.874.2348
 Technical Services: 800.USG.4YOU

Websites: usg.com
usgdesignstudio.com
sustainableceilings.com
seismicceilings.com

See usg.com for
 the most up-to-date
 product information.

30 Year System Warranty – No visible sag – Mold/mildew protection	UL Classified												
	Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ¹	Panel Cost
Radar <i>CLIMAPlus</i> Open Plan Panel	SQ	2'x2'x7/8"	Class A	22320	.75	35	.84	White	A, B, C	Low		51% HRC	\$
		2'x4'x7/8"	Class A	22325	.75	35	.84	White	A, C	Low		51% HRC	\$
	SLT	2'x2'x7/8"	Class A	22340	.75	35	.84	White	D	Low		51% HRC	\$
		2'x4'x7/8"	Class A	22345	.75	35	.84	White	D	Low		51% HRC	\$
	FLB	2'x2'x7/8"	Class A	22330	.75	35	.84	White	E, F, G, H	Low		51% HRC	\$
		2'x4'x7/8"	Class A	22335	.75	35	.84	White	E, F, G, H	Low		51% HRC	\$

Legend

Low Emissions (VOC Class)

Low-Emitting performance meets CA Specification 01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on CHPS data base for low-emitting materials. USG Certificate of Compliance for Low VOC Emissions also available on usg.com.

CLIMAPlus Superior Performance³

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold and mildew.

HRC High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Grid Profile Options

A DX®/DXL™	B CENTRICITEE™ DXT	C DXW™	D DX/DXL	E CENTRICITEE™ DXT	F FINELINE® DXF	G FINELINE® 1/8 DXFF	H IDENTITEE™ DXI™

Physical Data/ Footnotes

Product literature
 Data sheet: SC2565
ASTM E1264 classification
 Type III, Form 2, Pattern C, E
ASTM E84 surface burning characteristics
 Class A
 Flame spread: 25
 Smoke developed: 50

Weight
 .88 - 1.12 lb./sq. ft.
Thermal resistance
 R- 1.8 (7/8" panels)
Maximum backloading
 See Warranty for details.
Maintenance
 Panels can be cleaned easily with a soft brush or vacuum.

Footnotes
 1. For details, see LEED report tool at usgdesignstudio.com.
 2. LR values are shown as averages.
 3. Panel face and back surfaces treated with a proprietary, broad-spectrum antimicrobial standard formulation that inhibits and retards the growth of mold and mildew. For details, see *Ceiling Systems Limited*

Warranty Commercial Applications
 (SC2102) and *CLIMAPlus Ceilings Certification of Performance* (SC2451).



Manufactured by USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

The following are trademarks of USG Interiors, LLC or a related company: CENTRICITEE, CLIMAPlus, DOWN, DX, DXF, DXFF, DXI, DXL, DXT, DXW, FINELINE, IDENTITEE, RADAR, USG.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC2565/5-12
 © 2012 USG Interiors, LLC
 Printed in U.S.A.