

FINE FISSURED™ Open Plan

Square Lay-in & Tegular

medium texture

Recycled Content: **66%**

armstrong.com/greengenie

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
☑	☑	☑	☑	☑	☑
Location Dependent					

LEED for Schools


Acoustics	Low Emitting or CHPS
☑	☑

\$\$\$\$\$

Key Selection Attributes

- Excellent solution in mixed (open plan/ closed plan) office design
- Excellent combination of acoustical performance; Articulation Class (170), NRC (0.75), and CAC (35)
- Non-directional visual reduces installation time and scrap
- 30-Year Limited System Warranty against visible sag (excludes items 1755, 1757, 1759), mold/mildew, and bacterial growth

Detail



Fine Fissured Open Plan

Typical Applications

- Open plan offices
- Healthcare – assists in addressing HIPAA and FGI acoustical requirements
- Classrooms
- Libraries/media centers
- Lobbies/reception areas
- Computer rooms

Color



White (WH)


Visual Selection

Performance Selection

Dots represent highest level of performance.

Edge Profile	Suspension Detail Dwg. Pgs. 226-228	Item No.	Dimensions	 UL Classified	Acoustics		AC	Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	Durable	Recycle Program
					NRC	CAC							
													
FINE FISSURED Open Plan													
	1	1754 1754M	2' x 2' x 7/8" 600 x 600 x 22mm		0.75 ⌵	35	170 ⌵	Class A	0.86 ⌵	HumiGuard+ ⌵	BioBlock+ ⌵	Standard	Yes ⌵
	1	1755 1755M	2' x 4' x 7/8" 600 x 1200 x 22mm		0.75 ⌵	35	170 ⌵	Class A	0.86 ⌵	Standard		Standard	⌵
	31-34, 54	1758 1758M	2' x 2' x 7/8" 600 x 600 x 22mm		0.75 ⌵	35	170 ⌵	Class A	0.86 ⌵		⌵	Standard	⌵
	31-34, 54	1759 1759M	2' x 4' x 7/8" 600 x 1200 x 22mm		0.75 ⌵	35	170 ⌵	Class A	0.86 ⌵	Standard		Standard	⌵
	7	1756 1756M	2' x 2' x 7/8" 600 x 600 x 22mm		0.75 ⌵	35	170 ⌵	Class A	0.86 ⌵		⌵	Standard	⌵
	7	1757 1757M	2' x 4' x 7/8" 600 x 1200 x 22mm		0.75 ⌵	35	170 ⌵	Class A	0.86 ⌵	Standard		Standard	⌵

Suspension Systems



Item 1758-CAC 33 on 9/16" Interlude, Sonata, Suprafine

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification

Type III, Form 1, Pattern C E
Fire Class A

Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

VOC/Formaldehyde Emissions

Meets CA Dept. of Health Services Standard Practice for the testing of VOC Emissions and is listed on CHPS High Performance Products Database for Low-Emitting Materials.

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor – 2.3 (BTU units)
R Factor – 0.40 (Watts units)

30-Year Performance Guarantee & Warranty Information

See warranty details in the back of this catalog

Weight; Square Feet/Carton

1754, 1756, 1758 – 1.08 lbs/SF; 40 SF/ctn
1755, 1757, 1759 – 1.08 lbs/SF; 48 SF/ctn