

TUNDRA®

Square Lay-in & Tegular

medium texture

Recycled Content: **Up to 50%**

armstrong.com/greengenie

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
✓	✓	✓	✓	✓	✓

Location Dependent

LEED for Schools

Acoustics	Low Emitting or CHPS
	✓

\$\$\$\$\$

Key Selection Attributes

- Durable
 - Impact-resistant
 - Scratch-resistant
- 30-Year Limited System Warranty against visible sag, mold/mildew, and bacterial growth

Typical Applications

- Offices
- Schools
- Corridors

Color



White (WH)



Tundra with Suprafine® 9/16" Exposed Tee grid (Pg. 220)


Visual Selection

Performance Selection

Dots represent highest level of performance.

Edge Profile	Suspension Detail Dwg. Pgs. 226-228	Item No.	Dimensions	UL Classified		Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	Durable		Recycle Program	
				Acoustics NRC	CAC					Impact	Scratch		
TUNDRA													
9/16" Beveled Tegular	31-34, 54	304	2' x 2' x 5/8"	□	0.50	33	Class A	0.87	HumiGuard+	BioBlock+	Impact	Scratch	Yes
		304M	600 x 600 x 15mm										
15/16" Square Lay-in	1	301	2' x 2' x 5/8"	□	0.50	33	Class A	0.87					
		301M	600 x 600 x 15mm										
		839	2' x 2' x 5/8"	□	0.50	33	Fire Guard	0.87					
		839M	600 x 600 x 15mm										
15/16" Beveled Tegular	12	302	2' x 4' x 5/8"	□	0.50	35	Class A	0.87					
		302M	600 x 1200 x 15mm										
		840	2' x 4' x 5/8"	□	0.50	35	Fire Guard	0.87					
		840M	600 x 1200 x 15mm										
15/16" Beveled Tegular	12	303	2' x 2' x 5/8"	□	0.50	33	Class A	0.87					
		303M	600 x 600 x 15mm										
15/16" Beveled Tegular	12	305	2' x 4' x 5/8"	□	0.50	35	Class A	0.87					
		305M	600 x 1200 x 15mm										

Suspension Systems



Item 304-CAC 31 on 9/16" Interlude, Sonata, Suprafine

Physical Data

Material
Wet-formed high density mineral fiber

Surface Finish
Factory-applied latex paint with scuff-resistant spatter coat

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard™: A fire resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type III, Form 2, Pattern C E
Fire Class A

Sag Resistance
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

VOC/Formaldehyde Emissions
Meets CA Dept. of Health Services Standard Practice for the testing of VOC Emissions depending on ceiling use and building parameters. Contact TechLine to evaluate performance.

Anti Mold/Mildew & Bacteria
BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value
R Factor – 1.7 (BTU units)
R Factor – 0.30 (Watts units)

30-Year Performance Guarantee & Warranty Information
See warranty details in the back of this catalog

Weight; Square Feet/Carton
301, 302, 305 – 1.09 lbs/SF; 64 SF/ctn
303, 304 – 1.10 lbs/SF; 48 SF/ctn
839, 840 – 1.16 lbs/SF; 64 SF/ctn

