CIRRUS® Themes

Stars[™] & Things That Fly[™] Tegular fine texture





Cirrus Themes Stars with Suprafine® 9/16" Exposed Tee grid

Cirrus Themes Things That Fly with Suprafine 9/16" Exposed Tee grid

Key Selection Attributes

- · A variety of individual lighthearted panel designs on Cirrus refined texture; can be spot-painted
- Excellent sound absorption
- 30-Year Limited System Warranty against mold/mildew and bacterial growth
- Hardware Friendly Options are available for plain panels 295 and 299, providing precut finished edge details for fixture openings (1" to 16" diameter)

Typical Applications

- Healthcare assists in addressing HIPAA requirements
- · Pediatric areas
- · Lobbies/reception areas

- · Specialty shops/stores
- · Playful theme interiors

Face View Drawings

Cirrus Themes Stars



S400/S450



























Face View Drawings

Cirrus Themes Things That Fly













S420/S470

S421/S471















S707/S757





Cirrus Themes Panels

S703/S753 S704/S754





Detail and Grid Intersections



CIRRUS Beveled Tegular Plain Panel



CIRRUS Themes Stars with SUPRAFINE 9/16" Exposed Tee grid



Hardware Friendly Options

Color







CIRRUS® Themes

Stars[™] & Things That Fly[™] Tegular fine texture



\$\$\$\$\$

Visual Selection						Performance Selection Dots represent highest level of performance.								
Edge Profile CIRRUS Theme:	s Stars*	Item No.	Dimensions		Acous NRC	stics	Fire Rating	Light Reflect	Sag Resist	Anti- Microbial	VOC Formal- dehyde	Durable	Recycle Program	
9/16" Beveled Tegular		S400 Series S400M Series	2' x 2' x 3/4" 600 x 600 x 19mm		0.65	35	Class A	0.86	S	BioBlock+ ●	No Added	S	Yes •	
Angled Tegular CIRRUS Themes	e Things That I	S450 Series S450M Series	2' x 2' x 3/4" 600 x 600 x 19mm		0.65	35	Class A	0.86	S	•	No Added	S	•	
9/16" Beveled Tegular	s mings maci	S700 Series S700M Series	2' x 2' x 3/4" 600 x 600 x 19mm		0.65	35	Class A	0.86	S	•	No Added	S	•	
15/16" Angled Tegular	s Plain Panel _	S750 Series S750M Series	2' x 2' x 3/4" 600 x 600 x 19mm e with Hardware Fri	iendly	0.65 •	35 s (II S	Class A	0.86	S	•	No Added	S	•	
9/16" Beveled Tegular	3 1 Iaiii 1 aiici –	S299 S299M	2' x 2' x 3/4" 600 x 600 x 19mm		0.65	35	Class A	0.86	S	•	No Added	S	•	
15/16" Angled Tegular		S295 S295M	2' x 2' x 3/4" 600 x 600 x 19mm		0.65	35	Class A	0.86	S	•	No Added	S	•	
S * Note: Spec	ify Cirrus Themes p		AWI Licensing Company. S299/S295 when plain pa		e required	I.								
9/16"	Standard: Interlude®, Sonata™, Suprafine®													
15/16"	Standard: Prel	ude®												

Physical Data

Material

Wet-formed mineral fiber

Surface Finish Factory-applied latex paint

Fire Performance ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification

Type III, Form 1, Pattern E | K Z (scored multi-patterned finish) S299, S295 – Type III, Form 1, Pattern E I Fire Class A

No-Added Formaldehyde
No-added formaldehyde – free of formaldehyde-based
resins. Outperform CHPS Section 01350 requirements.
(Independent test reports available upon request.)

Anti Mold/Mildew & Bacteria BioBlock* Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value R Factor – 1.9 (BTU units) R Factor – 0.33 (Watts units)

Backloading RecommendationContact TechLine for specific information

30-Year Performance Guarantee & Warranty Information See warranty details at armstrong.com/warranty

Application Considerations
Specify matching plain panels S299/S295 when required. Not recommended for rooms containing MRI equipment.

Weight; Square Feet/Carton All design panels – 1.38 lbs/SF; 8 SF/ctn S295 – 1.09 lbs/SF; 48 SF/ctn S299 – 1.17 lbs/SF; 48 SF/ctn

