



Items 1772, 1773, 1774, 1775 & 1776



Dune with Prelude® XL 15/16" Exposed Tee grid (Pg. 215);
Axiom® Classic Trim (Pg. 236)



Dune with Interlude® 9/16" Dimensional Tee grid (Pg. 211);
Axiom® Classic Trim (Pg. 236)

Key Selection Attributes

- Upgrade look at a modest price
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 1774HRC, 1775HRC, 1776HRC, 1777HRC. 35% Pre-consumer; 18% Post-consumer
- Durable Scratch-resistant
- Non-directional visual reduces installation time and scrap
- 30-Year Limited System Warranty against visible sag (excludes items 1796 and 1798), mold/mildew, and bacterial growth

Typical Applications

- Offices
- Corridors
- Retail
- Hospitality
- Classrooms

Detail (Other Suspension Systems compatible. Refer to listing on page 156.)


Color




Dune




Dune Square Lay-in
with Prelude 15/16"
Exposed Tee grid



Dune Tegular with
Suprafine® 9/16"
Exposed Tee grid



Dune Tegular with
Interlude XL® 9/16"
Dimensional Tee grid



Dune Tegular with
Silhouette® 9/16"
Bolt-Slot grid
1/4" Reveal



White (WH)

DUNE™

Square Lay-in & Tegular

fine texture



The post-consumer recycled content of these items is from reclaimed ceilings

Recycled Content: Up to 53%

armstrong.com/greengenie

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
✓	✓	✓	✓	✓	✓
Location Dependent					

LEED for Schools

Acoustics	Low Emitting or CHPS
✓	✓

\$\$\$\$\$

Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Grid Drawings Cat. pgs. 226-228 or armstrong.com/catdwg	Item No.	Dimensions	UL Classified	Acoustics NRC	CAC	Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	Durable	Recycle Program
DUNE Square Lay-in												
	1	1772 1772M	2' x 2' x 5/8" 600 x 600 x 15mm		0.50	30	Class A	0.83	HumiGuard+	BioBlock+	Scratch	Yes
	1	1850 1850M	2' x 2' x 5/8" 600 x 600 x 15mm		0.50	35	Fire Guard	0.83	.	.	.	.
	1	1773 1773M	2' x 4' x 5/8" 600 x 1200 x 15mm		0.50	33	Class A	0.83	.	.	.	.
	1	1851 1851M	2' x 4' x 5/8" 600 x 1200 x 15mm		0.50	35	Fire Guard	0.83	.	.	.	.
	1	1796 1796M	20" x 5' x 3/4" 500 x 1500 x 19mm		0.50	35	Class A	0.83	Standard	.	.	.
	1	1798 1798M	30" x 30" x 3/4" 750 x 750 x 19mm		0.50	35	Class A	0.83	Standard	.	.	.
DUNE Tegular												
	31-34, 54	1775 1775M 1775HRC	2' x 2' x 5/8" 600 x 600 x 15mm 2' x 2' x 5/8"		0.50	35	Class A	0.83	.	.	.	.
	31	1852	2' x 2' x 5/8"		0.50	35	Fire Guard	0.83	.	.	.	.
	31-34, 54	1777 1777M 1777HRC	2' x 4' x 5/8" 600 x 1200 x 15mm 2' x 4' x 5/8"		0.50	35	Class A	0.83	.	.	.	.
	6	1774 1774M 1774HRC	2' x 2' x 5/8" 600 x 600 x 15mm 2' x 2' x 5/8"		0.50	35	Class A	0.83	.	.	.	.
	6	1853	2' x 2' x 5/8"		0.50	35	Fire Guard	0.83	.	.	.	.
	6	1776 1776M 1776HRC	2' x 4' x 5/8" 600 x 1200 x 15mm 2' x 4' x 5/8"		0.50	35	Class A	0.83	.	.	.	.

Suspension Systems

15/16"		9/16"	
	Prelude® Prelude XL® Fire Guard		Item 1775-CAC 33 on 9/16" Interlude, Sonata, Suprafine

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard™: A fire resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification

Type III, Form 2, Pattern C E
Fire Class A

Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

VOC/Formaldehyde Emissions

Meets CA Dept. of Health Services Standard Practice for the testing of VOC Emissions and is listed on CHPS High Performance Products Database for Low-Emitting Materials.

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor – 0.94 (lb/SF) units
R Factor – 0.28 (Watts units)

30-Year Performance Guarantee & Warranty Information

Details in back of catalog or at armstrong.com/warranty

Weight; Square Feet/Carton

1772 – 0.94 lbs/SF; 64 SF/ctn
1773 – 0.88 lbs/SF; 80 SF/ctn
1796 – 1.33 lbs/SF; 67 SF/ctn
1798 – 1.14 lbs/SF; 50 SF/ctn
1850 – 1.19 lbs/SF; 48 SF/ctn
1851 – 1.22 lbs/SF; 64 SF/ctn
1774, 1775 – 0.75 lbs/SF; 64 SF/ctn
1776, 1777 – 0.75 lbs/SF; 80 SF/ctn
1852, 1853 – 1.20 lbs/SF; 48 SF/ctn