

Recycled Content: 41%

armstrong.com/greengenie

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
✓	✓	✓	✓	✓	✓

Location Dependent

LEED for Schools

Acoustics	Low Emitting or CHPS
✓	✓

\$\$\$\$\$

FINE FISSURED™

Tile
medium texture

Key Selection Attributes

- 1' x 1' concealed tile option provides grid-hiding monolithic installation
- Non-directional visual reduces installation time and scrap
- 30-Year Limited System Warranty against visible sag, mold/mildew, and bacterial growth


Typical Applications

- Areas with minimal plenum conditions

Color



White (WH)



Fine Fissured Tile with Prelude Concealed grid (Pg. 212)

Visual Selection

Performance Selection

Dots represent highest level of performance.

Edge Profile	Grid Drawings Cat. pgs. 226-228 or armstrong.com/catdwg	Item No.	Dimensions	 UL Classified	Acoustics		Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	Durable	Recycle Program
					NRC	CAC						
FINE FISSURED Tile												
Concealed	45	746	1' x 1' x 5/8"		0.55	35	Class A	0.85	HumiGuard+	BioBlock+	Standard	Yes
												
Tongue & Groove	47	741	1' x 1' x 1/2"		0.55	N/A	Class A	0.85			Standard	
												

Suspension Systems

Concealed		Tongue & Groove	
	Prelude® Concealed, Adhesive		Staple up, Adhesive

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification

Type III, Form 2, Pattern C E
Fire Class A

Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

VOC/Formaldehyde Emissions

Meets CA Dept. of Health Services Standard Practice for the testing of VOC Emissions and is listed on CHPS High Performance Products Database for Low-Emitting Materials.

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

30-Year Performance Guarantee & Warranty Information

Details in back of catalog or at armstrong.com/warranty

Weight; Square Feet/Carton

741 – 0.75 lbs/SF; 40 SF/ctn
746 – 0.90 lbs/SF; 40 SF/ctn