

Recycled Content: 52%

armstrong.com/greengenie

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
	✓	✓	✓	✓	

Location Dependent

LEED for Schools

Acoustics	Low Emitting or CHPS
	✓

LEDGES®

Tegular
smooth texture

\$\$\$\$\$

Key Selection Attributes

- Dimensional, sculptured visual
- Affordable and practical alternative to embossed plaster panels
- Non-directional visual reduces installation time and scrap

Typical Applications

- Department stores/retail
- Many types of commercial interiors

Note: Not recommended for areas requiring acoustical performance

Color



White (WH)



Item 8013



Item 8011



LEDGES (item 8011)

Ledges (item 8013) with Suprafine® 9/16" Exposed Tee grid (Pg. 220)

Visual Selection

Performance Selection Dots represent highest level of performance.

Edge Profile	Suspension Detail Dwg. Pgs. 226-228	Item No.	Dimensions	UL Classified		Acoustics NRC	CAC	Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	Durable	Recycle Program
LEDGES													
9/16" Flush Tegular	4	8013	2' x 2' x 3/4"		N/A	35	Class A	0.80	Standard		Standard	Yes	
													
15/16" Flush Tegular	4	8011	2' x 2' x 3/4"		N/A	35	Class A	0.80	Standard		Standard		
													

Suspension Systems

15/16"		9/16"	
	Prelude®		Suprafine

Physical Data

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification

Type III, Form 2, Pattern J Z
Fire Class A

VOC/Formaldehyde Emissions

Meets CA Dept. of Health Services Standard Practice for the testing of VOC Emissions and is listed on CHPS High Performance Products Database for Low-Emitting Materials.

Anti Mold/Mildew & Bacteria

BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor - 1.6 (BTU units)
R Factor - 0.28 (Watts units)

Warranty Information

See warranty details in the back of this catalog

Weight; Square Feet/Carton

0.90 lbs/SF; 48 SF/ctn