

ULTIMA®

Tegular

fine texture



Items 1911, 1912, 1914, 1915



Ultima Beveled Tegular with Suprafine® 9/16" Exposed Tee grid (Pg. 220)
Axiom® Classic Trim; Drywall Grid Soffit (Pg. 236)



Ultima Beveled Tegular with Sonata® 9/16" Dimensional Tee grid (Pg. 219)
Axiom® Classic Trim; Drywall Grid Soffit (Pg. 236)


Key Selection Attributes

- Smooth, clean, durable finish – Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- NEW** • Scrubbable and water-repellent (items 1936, 1937)
- Excellent sound absorption
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 1911HRC, 1912HRC, 1914HRC, 1915HRC. 65% Pre-consumer; 15% Post-consumer
- Visual coordinates with Optima® for mixed (open/closed plan) applications
- Non-directional visual reduces installation time and scrap
- Compatible with the TechZone™ Ceiling Systems. Items 1905, 1911, 1912, 1914, 1915 only.
- Smaller size panels available (1 carton min. order). Info: armstrong.com/specials
- Excellent sound blocking – items 1951, 1952
- Plank sizes available (search: Ultima Plank)
- Meets USDA/FSIS guidelines for use in food processing areas (items 1936 and 1937)
- 30-Year Limited System Warranty against visible sag (excludes item 1905), mold/mildew, and bacterial growth

Typical Applications

- Offices
- Healthcare – assists in addressing HIPAA and FGI acoustical requirements
- Classrooms
- Corridors
- Lobbies/reception areas
- Department stores/retail
- Areas requiring frequent plenum access
- Areas with indirect lighting systems
- Kitchens, dining rooms, and food preparation areas (items 1936 and 1937)

Detail (Other Suspension Systems compatible. Refer to listing on page 186.)



Ultima
Beveled Tegular



Ultima High Washability
Tegular



Ultima with
Suprafine 9/16"
Exposed Tee grid



Ultima with
Silhouette® XL® 9/16"
Bolt-Slot 1/4" Reveal grid

Color



White (WH)

ULTIMA®

Tegular

fine texture



The post-consumer recycled content of these items is from reclaimed ceilings

Recycled Content: Up to 80%

armstrong.com/greengenie

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
✓	✓	✓	✓		✓

Location Dependent

LEED for Schools

Acoustics	Low Emitting or CHPS
✓	✓

65% Pre-consumer; 15% Post-consumer

\$\$\$\$\$


Visual Selection

Performance Selection

Dots represent highest level of performance.

Edge Profile	Suspension Detail Dwg. Pgs. 236-238	Item No.	Dimensions	UL Classified	Acoustics NRC CAC	Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	Durable Wash Scrub Water Impact Scratch Soil	Recycle Program
ULTIMA Tegular											
9/16" Beveled Tegular	31-34, 54	1916 1916M	1' x 2' x 3/4" 300 x 600 x 19mm	□	N/A N/A	Class A	0.90	HumiGuard+	BioBlock+	Wash Scrub Water Repel	Yes
	31-34, 54	1912 1912M 1912HRC	2' x 2' x 3/4" 600 x 600 x 19mm 2' x 2' x 3/4"	□	0.70 35	Class A	0.90				
	31-34, 54	1952 1952M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.60 40	Class A	0.90				
	31-34, 54	1915 1915M 1915HRC	2' x 4' x 3/4" 600 x 1200 x 19mm 2' x 4' x 3/4"	□	0.70 35	Class A	0.90				
	31-34, 54	1905 1905M	30" x 30" x 3/4" 750 x 750 x 19mm	□	0.70 35	Class A	0.90	Standard			
15/16" Beveled Tegular	12	1917 1917M	1' x 2' x 3/4" 300 x 600 x 19mm	□	N/A N/A	Class A	0.90				
	12	1911 1911M 1911HRC	2' x 2' x 3/4" 600 x 600 x 19mm 2' x 2' x 3/4"	□	0.70 35	Class A	0.90				
	12	1951 1951M	2' x 2' x 3/4" 600 x 600 x 19mm	□	0.60 40	Class A	0.90				
	12	1914 1914M 1914HRC	2' x 4' x 3/4" 600 x 1200 x 19mm 2' x 4' x 3/4"	□	0.70 35	Class A	0.90				
NEW ULTIMA High Washability (see Health Zone™ Ultima, Pg. 173)											
9/16" Beveled Tegular	31-34, 54	1936	2' x 2' x 3/4"	□	0.70 35	Class A	0.86				
15/16" Beveled Tegular	12	1937	2' x 2' x 3/4"	□	0.70 35	Class A	0.86				

Suspension Systems



Item 1912-CAC 33 9/16" Interlude, Sonata, Suprafine

Physical Data

Material
Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane
1936, 1937 – Wet-formed mineral fiber with DuraBrite acoustically transparent water-repellent membrane

Surface Finish
DuraBrite with factory-applied latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification
Type IV, Form 2, Pattern E
Fire Class A

Sag Resistance
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

VOC/Formaldehyde Emissions
Meets CA Dept. of Health Services Standard Practice for the testing of VOC Emissions and is listed on CHPS High Performance Products Database for Low-Emitting Materials.

Anti-Mold/Mildew & Bacteria
BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value
R Factor – 2.2 (BTU units)
R Factor – 0.39 (Watts units)

30-Year Performance Guarantee & Warranty Information
See warranty details at armstrong.com/warranty

Application Considerations (All items except HRC)
1' x 2' products intended for use with 1' x 2' recessed lighting fixtures and are not UL Classified for acoustics.

Cleaning Recommendations (Items 1936, 1937 only)
To clean panel, use a clean, white cloth with water or a mild detergent and wipe surface. To disinfect panel, lightly spray surface and wipe clean with a clean, white cloth. Acceptable colorless disinfectants include:
• Sodium hypochlorite • Hydrogen peroxide
• Isopropyl alcohol • Quaternary ammonium

Weight; Square Feet/Carton
1905 – 1.05 lbs/SF; 62.5 SF/ctn
1911, 1912, 1914, 1915 – 1.05 lbs/SF; 48 SF/ctn
1916, 1917 – 1.05 lbs/SF; 24 SF/ctn
1936, 1937 – 1.08 lbs/SF; 48 SF/ctn
1951, 1952 – 1.31 lbs/SF; 48 SF/ctn