ULTIMA® Themes™

Blooms, Bubbles, Dragonflies, Stars Tegular, Vector®

fine texture









Ultima Themes Stars 2' x 2' with Prelude 15/16" Exposed Tee grid (Pg. 215)

Ultima Themes Bubbles 2' x 2' on Silhouette 9/16" grid (Pg. 217)

Key Selection Attributes

- · A variety of subtle, artistic images on Ultima fine texture
- · Smooth, clean, durable finish -Washable, Impact-resistant, Scratch-resistant, Soil-resistant
- Excellent sound absorption
- Now available with Ultima® Create!™ custom colors and images
- · Visual coordinates with Optima® for mixed (open/closed plan) applications
- Available on Health Zone™ Ultima for spaces that require frequent cleaning or disinfection
- · 30-Year Limited System Warranty against visible sag, mold/mildew, and bacterial growth

Typical Applications

- Healthcare assists in addressing HIPAA and FGI acoustical requirements
- Hospitality
- · Department stores/retail
- · Lobbies/reception areas
- Classrooms
- Offices

Detail (Other Suspension Systems compatible. Refer to listing on page 194.)



Ultima Themes Beveled



Ultima Themes Beveled Tegular with Suprafine 9/16" Exposed Tee grid



Ultima Themes Vector



Ultima Themes Vector with Prelude 15/16" Exposed Tee grid

Color



Face View Drawings — Images printed grayscale as shown. Contact your Armstrong Rep for details.

Ultima Themes Blooms



4-Panel Design Item 022 (Add A, B, C, or D for

Ultima Themes Dragonflies 2' x 2'





4-Panel Design Item 052 (Add A, B, C, or D for individual panel

Ultima Themes Stars 2' x 2'





Single Panel Item 043









Davlight

LEED for Schools

Energy Waste Recycled Mgmt

Items Z1911HRC, Z1912HRC are available with High Recycled Content as a special order

LEED® Credits

Recycled

Content Materials Materials V

Local

Renewable & Views Location Dependent

Tegular, Vector®

ULTIMA® Themes™

Blooms, Bubbles, Dragonflies, Stars

Edge Profile ULTIMA Them	Grid Drawings Cat. pgs. 226-228 or armstrong.com/ catdwg es Tegular	Item No.*	Dimensions		Acous NRC		Fire Rating	Light Reflect	Sag Resist	Anti- Microbial			Durabl		<u></u>	Recycle Program
9/16" Beveled Tegular	31-34, 54	Z1912A	2' x 2' x 3/4" Single panel designs 4' x 4' x 3/4" Four-panel designs		0.70	35	Class A	0.90	HumiGuard+ ●	BioBlock+	Wash •	Water Repell. —	Impact •	Scratch	Soil	Yes
15/16" Beveled Tegular	12	Z1911A	2' x 2' x 3/4" Single panel designs 4' x 4' x 3/4" Four-panel designs		0.70	35	Class A	0.90	•	•	•	-	•	•	•	•
ULTIMA Themes Vector																
1/4" reveal with 15/16" vector	20	Z1920A	2' x 2' x 3/4" Single panel designs 4' x 4' x 3/4" Four-panel designs		0.70	33	Class A	0.90	•	•	•	-	•	•	•	•
Health Zone™	ULTIMA (See He	alth Zone Ulti	ma CS-4066)													
9/16" Beveled Tegular	31-34, 54	Z1936	2' x 2' x 3/4"		0.70	35	Class A	0.86	•	•	•	•	•	•	•	•

* When specifying or ordering, include the appropriate 3-digit design suffix (e.g., Z1912A022)

Z1937 _ _ _

Suspension Systems - ULTIMA Themes Tegular

15/16' 9/16' 广门 Prelude[®] Interlude® XL® Silhouette® XL Sonata® XL Suprafine® Trimlok® Screw-Slot 1/4" or 1/8" Reveal

0.70

35

Class A 0.86

2' x 2' x 3/4"


Item Z1912A-CAC 33 on Interlude, Sonata, Suprafine

12, 2A

Suspension Systems - ULTIMA Themes Vector

15/16' Prelude®

Suspension Systems - ULTIMA Health Zone Themes



Physical Data

Material

15/16"

Printed on recyclable paper with vegetable-based inks.

Beveled Tegular

Wet-formed mineral fiber with DuraBrite® acoustically transparent membrane

Surface Finish

DuraBrite with factory-applied latex paint with solvent free ultraviolet ink

Fire Performance

CS-4110-1111

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled)

ASTM E1264 Classification Type IV, Form 2, Pattern E Fire Class A

Sag Resistance

HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

VOC/Formaldehyde Emissions

Meets CA Dept. of Health Services Standard Practice for the testing of VOC Emissions and is listed on CHPS High Performance Products Database for Low-Emitting

Anti-Mold/Mildew & Bacteria BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value

R Factor – 2.2 (BTU units) R Factor – 0.39 (Watts units)

30-Year Performance Guarantee & Warranty Information

Details in back of catalog or at armstrong.com/warranty

Weight; Square Feet/Carton Z1911A, Z1912A – 1.05 lbs/SF; 16 SF/ctn Z1920A – 1.08 lbs/SF; 16 SF/ctn Z1936, Z1937 - 1.08 lbs/SF; 48 SF/ctn

irmstrona

ER