
Ecophon® Focus™ E

DESIGNER SERIES HIGH DENSITY FIBERGLASS CEILINGS

CertainTeed

Specification Sheet







REVEAL EDGE



NARROW REVEAL EDGE 9/16" Grid

Applications: Public Lobbies

- · Conference Rooms
- Offices
- Galleries
- Libraries
- Resorts

Features & Benefits:

- · Superior sound absorption.
- Suitable clean room component to ISO class 5 (class 100).
- Akutex FT white finish has perfect light diffusion (+99%).
- · Available in 9 colors.
- · Moisture resistant.
- · Recommended by Swedish Asthma and Allergy Association.


See reverse for additional product specifications.

Attributes:

| ITEM NUMBER | NOMINAL SIZE (Inches) | EDGE DETAIL | NRC | CAC | AC | LR | RECYCLED CONTENT % | | ISO SOUND | | | | |
|-------------------------|--------------------------|---------------|------|-----|-----|------|--------------------|-----|---------------------|--|--|--|--|
| | | | | | | | Post | Pre | ABSORPTION CLASS | | | | |
| ECOPHON® FOCUS™ E | | | | | | | | | | | | | |
| 3542 2263 | 24 x 24 x 3/4 | Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| 3542 2264 | 24 x 48 x 3/4 | Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| 3542 2265 | 48 x 48 x 3/4 | Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| ECOPHON® FOCUS™ E/24 XL | | | | | | | | | | | | | |
| 3542 5070 | 24 x 60 x 3/4 | Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| 3542 5071 | 24 x 72 x 3/4 | Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| 3542 5073 | 24 x 96 x 3/4 | Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| ECOPHON® FOCUS™ E/15 | | | | | | | | | | | | | |
| 3542 5929 | 24 x 24 x 3/4 | Narrow Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| 3542 5932 | 24 x 48 x 3/4 | Narrow Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| 3542 2287 | 48 x 48 x 3/4 | Narrow Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| ECOPHON® FOCUS™ E/15 XL | | | | | | | | | | | | | |
| 3542 5103 | 24 x 60 x 3/4 | Narrow Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| 3542 5104 | 24 x 72 x 3/4 | Narrow Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |
| 3541 5816 | 24 x 96 x 3/4 | Narrow Reveal | 0.90 | 23 | 180 | 0.85 | 70 | 1 | Α | | | | |

ASTM E 1264 Classification: Type XII, Form 2, Pattern G, Fire Class A

Acoustics:



SOUND ABSORPTION: Test results according to ASTM C 423. o.d.s = overall depth of system

····· Ecophon® Focus™ E 400 mm o.d.s.

| UNIT SIZE TESTED | SOUND ABSORPTION COEFFICIENTS – E-400 MOUNTING | | | | | | | | | | | |
|-------------------|--|-------|-------|--------|--------|--------|--|--|--|--|--|--|
| (Inches) | 125Hz | 250Hz | 500Hz | 1000Hz | 2000Hz | 4000Hz | | | | | | |
| ECOPHON® FOCUS™ E | | | | | | | | | | | | |
| 24 x 24 x 3/3 | 0.74 | 0.83 | 0.74 | 0.95 | 1.03 | 1.04 | | | | | | |











Product Specification Details Acoustical Ceilings 09 51 00

PART 2: PRODUCTS

2.1 GENERAL

Provide Acoustical Ceiling Material manufactured to meet requirements of this specification in accordance with ASTM E 1264.

2.2 MATERIALS

Acoustical Ceiling Units:

- 1. Type XII
- 2. Form 2
- 3. Pattern G
- 4. High density fiberglass panels with painted edges
- 5. Size [3/4"] thick x [24" x 24"] [24" x 48"] [24" x 60"] [24" x 72"] [24" x 96"] [48" x 48"]
- 6. Edge Detail Reveal
- 7. Noise Reduction Coefficient (NRC) 0.90
- 8. Articulation Class (AC) 190
- 9. Sound Absorption Class A
- 10. Ceiling Attenuation Class (CAC) 23
- 11. Light Reflectance Coefficient (LR) 0.85
- 12. Recycled Content [70 post] [1 pre]
- 13. Color [White] [Misty Rose] [Pale Garden] [Pure Olive] [Silent Sand] [Silver Shadow] [Soft Slate] [Vanilla Dream] [Volcanic Dust]
- 14. Flame Spread Classification (ASTM E 84, CAN/ULC-S102M) Class A
- 15. Manufacturer, subject to compliance with requirements of this specification, CertainTeed Ceilings
- 16. Product Name Ecophon® Focus™ E

Suspension Systems:

- 1. Profile [9/16" Face] [15/16" Face]
- 2. Manufacturer CertainTeed Ceilings Systems
- 3. Product Names [15/16" Classic Stab] [15/16" Classic Hook] [15/16" Classic Environmental Stab] [15/16" Classic Aluminum Capped Stab] [15/16" Classic Aluminum Capped Hook] [9/16" Elite Narrow Stab] [9/16" Smoothline Bolt Slot]
- 4. Warranty 15-year Limited Warranty when CertainTeed suspension system is installed together with any CertainTeed ceiling panel

Characteristics, properties or performance of materials or systems manufactured by CertainTeed herein described are derived from data obtained under controlled test conditions. CertainTeed makes no warranties, express or implied, as to their characteristics, properties or performance under any variations from such conditions in actual constructio CertainTeed assumes no responsibility for the effects of structural movement.

NOTICE: The information in this document is subject to change without notice. CertainTeed assumes no responsibility for any errors that may inadvertently appear in this document.

ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING . SIDING . TRIM . DECKING . RAILING . FENCE . FOUNDATIONS GYPSUM • CEILINGS • INSULATION • PIPE

Consumer: 800-782-8777

www.certainteed.com http://blog.certainteed.com Professional: 800-233-8990

CertainTeed Corporation

Valley Forge, PA 19482

P.O. Box 860

© 02/12 CertainTeed Corporation Code No. CTC-4823

