



MODULAR SPECIFICATIONS

Style Name	Filtering Through Modular
Style Number	GT144
Collection	Play of Light
Brand	Lees
Product Type	Modular
Minimum Sq. Yd.	No minimum
Construction	Tufted
Surface Texture	Level Patterned Loop
Gauge	1/12 (47.00 rows per 10 cm)
Density	6118
Weight Density	159,068
Sustainable Content	Contains up to 15% rapidly renewable content by total weight and a minimum 35% pre-consumer recycled content by total weight
Stitches Per Inch	12.2 (48.03 per 10 cm)
Finished Pile Thickness	.153 (3.89 mm)
Dye Method	Solution Dyed / Space Dyed
Backing Material	EcoFlex ICT
Face Yarn	SmartStrand® Contract made with DuPont™ Sorona® triexta, DuPont™ Sorona® Contains 37% rapidly renewable sourced ingredients by weight
Face Weight	26.0 oz per sq. yd. (882 g/m2)
Pattern Repeat	Not Applicable
Size/Width	24" x 24" (.6096 m x .6096 m)
Protective Treatment	Sentry Soil Protection
Installation Method	Quarter Turn, Brick Ashlar, Vertical Ashlar, Monolithic, Multi Directional
IAQ Green Label Plus	1258
Performance Rating	Heavy Traffic
Static	AATCC-134 Under 3.5 KV
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Warranties	Lifetime Limited Modular Warranty Lifetime Limited Stain WarrantyLifetime Static



139
DAYBREAK



559
EQUINOX



657
MIDSUMMER



841
SOLAR



866
AURORA



879
ECLIPSE



883
DAWN



966
LUNAR



989
SHADOW