



MODULAR SPECIFICATIONS

Style Name	Radiating Out Modular
Style Number	GT146
Collection	Play of Light
Brand	Lees
Product Type	Modular
Minimum Sq. Yd.	No minimum
Construction	Tufted
Surface Texture	Level Multi-Colored Loop
Gauge	1/12 (47.00 rows per 10 cm)
Density	7038
Weight Density	183,988
Sustainable Content	Contains up to 15% rapidly renewable content by total weight and a minimum 35% pre-consumer recycled content by total weight
Stitches Per Inch	13.4 (52.76 per 10 cm)
Finished Pile Thickness	.133 (3.38 mm)
Dye Method	Solution Dyed / Space Dyed
Backing Material	EcoFlex ICT
Face Yarn	SmartStrand® Contract made with DuPont™ Sorona® triexta, DuPont™ Sorona® Contains 37% rapidly renewable sourced ingredients by weight
Face Weight	26.0 oz per sq. yd. (882 g/m ²)
Pattern Repeat	Not Applicable
Size/Width	24" x 24" (.6096 m x .6096 m)
Protective Treatment	Sentry Soil Protection
Installation Method	Quarter Turn, Brick Ashlar, Vertical Ashlar, Monolithic, Multi Directional
IAQ Green Label Plus	.1258
Performance Rating	Heavy Traffic
Static	AATCC-134 Under 3.5 KV
Flammability	ASTM E 648 Class 1 (Glue Down)
Smoke Density	ASTM E 662 Less than 450
Warranties	Lifetime Limited Modular Warranty Lifetime Limited Stain Warranty Lifetime Static



129
BRIGHTSIDE



378
DUSK



549
NORTHERN LIGHTS



677
MORNING GLORY



831
SUNDANCE



876
AFTERGLOW



899
PITCH DARK



956
OVERCAST



979
SILHOUETTE