# Style Specifications — Victory Series

All floors shown or listed in this specification shall be Victory Series by Centiva, Florence, AL, 35630.

Specific product shall be: _ _ _ _ _ _ _ V _ _ _ _ in size _ _" × _ _"
Style Color Series Surface Edge

The Centiva Victory Series shall be homogeneous or constructed with a .032" (.80 mm) high density wearlayer depending on product. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each style. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 Wet Set, CENTI 6000 SP (Special Purpose) *(excluding Victory Magics, Coral Reef, and Mineral Chip products), or CENTI 2000 EP (epoxy). Installation shall be in accordance with the latest Centiva Installation Guidelines.

## VICTORY – GL 5029-V Glitter Royal

| | | | |
|---|---|---|---|
| **Classification:** | ASTM F 1700 Class III Solid Vinyl Tile | | |
| **Construction:** | Multiple layers with glitter in wearlayer and pre-consumer recycled backing | | |
| **Overall Thickness:** | .120" / 3 mm (nominal) | | |
| **Wearlayer Thickness:** | .032" clear, rigid high density PVC | | |
| **Size:** | 12" x 12", 12" x 18", 12" x 36", or 18" x 18" plus additional custom sizes | | |
| **Edge:** | Square Edge (SE) or Slight Bevel (SB) | | |
| **Surface Texture:** | Frost (FR) recommended. Additional surface textures available upon request. | | |
| **Warranty:** | 20 years Commercial, Lifetime Residential | | |
| **Recycling:** | Suitable | | |
| **Test Performance:** | ASTM E 648 | Critical Radiant Flux | Class1 CRF>0.45 |
| | ASTM E 662 | Smoke Density | <450 |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ADA Compliant Varies with surface texture | |
| | | FTC Slip Resistant Classified Product | |