

PHYSICAL CONSTRUCTION

Construction	Through-Pattern Vinyl Composition Tile
Size	12" x 12" (305 mm x 305 mm)
Overall Thickness	.125 inches (3.2 mm)
Package/Count	45 Per Carton
Coverage Per Carton	5 sq. yds.
Average Weight	65 lbs. per carton (29.5 kg per carton) 1.4 lbs. per tile (0.6 kg per tile)
Boxes Per Pallet	30

ENVIRONMENTAL

Recycled Content	2% Post-Consumer Recycled Content
FloorScore Indoor Air Quality	SCS Certified
CHPS 01350 Indoor Air Quality	Passed and Listed
NSF / ANSI-332 CERTIFICATION:	Gold
Manufacture Location	Salem, NJ USA

TESTING

ASTM Specification (F-1066)	Class 2
HUD / FHA Requirements	Exceeds
Flooring Radiant Panel Test (ASTM-E-648)	>.45 watts / cm ² , Passes – Class 1
N.B.S. Smoke Chamber Test (ASTM-E-662)	<450 Passes
Static Coefficient of Friction	Exceeds ADA Guidelines
Static Load Limit	125 p.s.i (8.79 kg / cm ²)

WARRANTY

Premium Tile Warranty	Limited 5 Year Commercial Warranty
-----------------------	------------------------------------

INSTALLATION

Installation Adhesive	Mannington M-Guard V-11, Full Spread *
-----------------------	--

- Color and pattern extend through the thickness of the tile.
- Premium Tile is not recommended for use in hospital operating suites, commercial kitchens, or in areas that require static dissipation.
- Darker colors of premium tile may be subject to scratch whitening, requiring more frequent maintenance.
- Wood subfloors directly on concrete or sleepers, either on or below grade, are unsatisfactory for Premium Tile installation.
- Dirt, wetness, finish selection and maintenance schedule may cause significant variation in actual performance.
- Premium Tile is not recommended in commercial areas where the surface temperature over radiant heated substrate exceeds 90°
- *Verify substrate (concrete) is dry per ASTM F-1869 8 lbs. maximum MVTR or ASTM F-2170 85% maximum relative humidity.
- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit and other substances from being tracked onto floor.