



# norament<sup>®</sup> luxor

## Product Description:

A rubber floor covering manufactured by nora systems, Inc. that is approved by Lloyd's Register Quality Assurance to the Quality Assurance Management System Standard ISO 9001:2000. Also ISO 14001 Environmental Management Systems certified.

## Resilient tile flooring for commercial traffic

1. Product Name: norament<sup>®</sup> luxor, Article 256
2. Material: nora vulcanized rubber compound 986 with abundant natural fillers and environmentally compatible color pigments
3. Surface: Mat-silk, smooth
4. Color: As selected
5. Tile Size: 0.14 inches (3.5mm) overall thickness, 19.8 inches by 19.8 inches (503mm by 503mm)
6. Back of Tile: Smooth, double-sanded back
7. Composition: Homogeneous rubber compound 986 with mottled design
8. Limited Wear Warranty: 10 years
9. Hardness: ASTM D2240, Shore type A, required  $\geq 85$
10. Static Load: Per ASTM F970 Standard Test Method for Static Load Limit, residual compression, when tested with 800 lbs.,  $\leq 0.005"$
11. Quality of Cut: ASTM F511  $\leq 0.005"$
12. Squareness: ASTM F2055  $\leq 0.010"$
13. ISO 14001: Manufacturer shall be ISO 14001 Environmental Management Systems Certified
14. PVC Free: Product shall contain no polyvinyl chloride
15. Abrasion Resistance: Taber abrasion test, ASTM D3389, H-18 wheel, 500 gram load, 1000 cycles, gram weight loss  $\leq 0.4$
16. Slip Resistance: Static coefficient of friction (James Test): ASTM D2047,  $\geq 0.8$
17. Bacteria Resistance: Product shall be resistant to bacteria, fungi, and micro-organism activity, according to ASTM E2180 and ASTM G21
18. Halogen Free: Product shall contain no halogens
19. Sound Absorption: 8 dB per ISO 140-8
20. Burn Resistance: Cigarette and solder burn resistance
21. Heat Resistance: Avg. Delta E  $< 8.0$  per ASTM F1514
22. Flammability: ASTM E648; NFPA 253; NBSIR 75 950,  $\geq 0.45$  watts per square centimeter, Class 1
23. Smoke Density: ASTM E662, NFPA 258, NBS smoke density,  $< 450$
24. Asbestos Free: Product shall contain no asbestos
25. Non Hazardous: Flooring shall be made without any chemicals that may be hazardous or containing any teratogenic, mutagenic or any other ingredients known to be carcinogenic
26. Cleaning: Flooring surface shall have the ability to be cleaned and maintained without the use of any chemicals that may be hazardous or containing any teratogenic, mutagenic or any other ingredients known to be carcinogenic. Flooring shall be cleanable using Green Seal certified products
27. Installation System: Use only nora<sup>®</sup> pro install system products following the current nora Installation Guide that may consist of part or all of the following steps depending upon the substrate conditions and requirements of the specific project.
  - Step 1 – nora<sup>®</sup> membrane (see Installation Guide for requirements).
  - Step 2 – nora<sup>®</sup> primer (see Installation Guide for requirements).
  - Step 3 – nora<sup>®</sup> leveler (see Installation Guide for requirements).
  - Step 4 – nora<sup>®</sup> patch (see Installation Guide for requirements).

Step 5 – nora® adhesives, the flooring usage and substrate conditions will determine the appropriate adhesive. Contact your nora representative for specific recommendations.

For more information, please refer to the MSDS, Installation Guides and Guide Specifications available on [www.nora.com/us](http://www.nora.com/us).

*Dated: March 2012*

**nora systems, Inc.**

9 Northeastern Blvd.

Salem, NH 03079

Toll free: 800-332-NORA

Phone: (603) 894-1021

Fax: (603) 894-6615

E-mail: [info-us@nora.com](mailto:info-us@nora.com)

[www.nora.com/us](http://www.nora.com/us)