

norament®

Test											
Product	grano	grano ed	ingresso	luxor	round & hammered	serra	strada	920	992	992 grano	norament® stairtreads
Article	1880 1912 stairtread	1880 1912	1880 3042	256	1902 1910	3016	1870	465 stairtread	1955	1955	465/466 467/468 469/479
Limited Wear Warranty in years	10	10	10	10	10	10	10	10	5	5	10
10-year nora® pro install system warranty*	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Taber Abrasion ASTM D3389 H-18 Wheel (1000 cycles) 500 gram load—grams weight loss	< .4	< .4	< .4	< .4	< .4	< .4	< .4	< .4	< .4	< .4	< .4
Shore Hardness "A" ASTM D2240	≥ 75	≥ 75	≥ 75	≥ 75	≥ 75	≥ 75	≥ 75	≥ 75	≥ 70	≥ 70	≥ 75
Rolling Load Limit/PSI (2) (Forklift Traffic)	850 (yes)	850 (yes)	Caster chair (no)	850 (yes)	550 (no)	850 (yes)	850 (yes)	850 (yes)	850 (yes)	850 (yes)	n/a
Static Load Limit 800 Lbs./Sq. In. ASTM F970 Residual Compression	≤ .005"	≤ .005"	≤ .005"	≤ .005"	≤ .005"	≤ .005"	≤ .005"	≤ .005"	≤ .005"	≤ .005"	≤ .005"
Static Coefficient of Friction ASTM D2047	Slip resistance (Tiles, Stairtreads) ≥ .8 Inquire about suitable products for ramps.										
Critical Radiant Flux ASTM E648 (not less than .45 W/per cm²)	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1	Class 1
NBS SMOKE DENSITY ASTM E662	< 450	< 450	< 450	< 450	< 450	< 450	< 450	< 450	< 450	< 450	< 450
Tunnel Test ASTM E84	—	—	—	—	—	—	—	Class A	—	—	—
Cigarette burn and solder resistance	Yes										
Halogen-free	Yes										
Resistance to: acids—alkalies—solvents—other chemicals (1)	EXCELLENT, CALL FOR SPECIFICS										
Oil and grease resistance	Yes	Yes	Yes	No	No	Yes	Yes	No	No	No	Yes
Static Generation Comparison Less than 10 Volts per ESD STM 97.2**	—	< 20	—	—	—	—	—	—	—	—	—
ESD-S7.1/ASTM F150 RH > 30% at room temperature 10 Year Limited Conductivity Warranty (ohms)	—	10⁶ < 10⁹	—	—	—	—	—	—	—	—	—
Decay-time FTM 101 C 4046 (sec.)	—	< .25	—	—	—	—	—	—	—	—	—
GREENGUARD Indoor Air Quality Certified®	Yes	***	***	Yes	Yes	Yes	Yes	***	***	***	Yes
GREENGUARD Children and Schools™ Certified	Yes	***	***	***	Yes	Yes	Yes	***	***	***	Yes
CA 01350 Compliant	Yes	***	***	Yes	Yes	Yes	Yes	***	***	***	Yes

(1) Call nora systems, Inc. for details.

(2) No metal or hard plastic wheels, the shape of contact surfaces of equipment wheels must be flat, and the wheels shall be ≤ 90 shore hardness type A.

*Registration for 10-year nora pro install system warranty required.

**Tested with conductive shoes.

***Not yet tested.

nora systems, Inc.

9 Northeastern Blvd.

Salem, NH 03079

Toll free: 800-332-NORA

Phone: (603) 894-1021

Fax: (603) 894-6615

E-mail: info-us@nora.com

www.nora.com/us

nora®

All About Flooring. All About You.