



## HEIRLOOM RESILIENT CORK FLOOR TILE

### TECHNICAL DATA

Cork is a naturally resilient product with unparalleled durability, suitable for both commercial and residential installations. Because cork is a natural product, shade variations are normal, adding to the beauty of the natural flooring surface.

**Standard Dimensions:** 12" X 12" and 24" x 24"

**Standard Planks:** 4"x12", 4"x24", 6"x12", 6"x24"

**Custom Sizes:** Custom cuts available up to 36" in length

**Thickness:** 1/2" (12mm)

**Construction:** High density, pre consumer homogenous cork granules.

**Surface Finishes:**

Polyurethane: 3 coats of water-based matte polyurethane applied at factory.

3 additional coats required for commercial uses and high traffic areas.

Unfinished: Pre-sanded at the factory.

Must be finished on site. Can be stained before finishing.

**Density:** ≤ 35 lbs. per cubic foot

**Storage Conditions:** Material shall be stored and installed where relative humidity is between 45% and 75%, and the temperature is between 65°F and 80°F. Material MUST be left in unopened original packaging prior to installation for at least 72 hours in area where it is to be installed.

**Residual Indentation:** Cork flooring has the ability to recover up to 100% from indentations. However, when excessive pinpoint pressure is applied (i.e. stiletto heels, improper furniture and appliance footings) cork will NOT recover completely.

**Fire Test ASTM E648-08:** Class I

**Fire Test ASTM E84-12:** Class II

**Coefficient of Friction (ASTM D-2047-93):** Exceeds all ADA recommendations for slip resistance.

**Acoustical Data:**

- ASTM E 492-90/ASTM E 989-89 (STC rating)
  - 1/2" = 54 dB
- ASTM E 90-02 (IIC rating)
  - 1/2" = 58 dB

**Cork will fade in direct sunlight.**

For more information visit [www.expanko.com](http://www.expanko.com) or call 800-345-6202.