



## REZTEC AND REZTEC CHUNKS RUBBER FLOORING

### TECHNICAL SPECIFICATIONS

TECHNICAL SUPPORT 800.345.6202

**Suitability:** Heavy use Commercial and Residential

**Moisture Resistance:** Reztec is highly resistant to moisture and is suitable for use in locker rooms and other areas subjected to surface moisture.

<b>Standard Dimensions:</b>	Roll Goods - (Maximum Lengths):			
	<i>Thickness</i>	<i>Dimensions</i>	<i>Square Feet</i>	<i>Weight/ft<sup>2</sup></i>
	4.0 mm	4' X 58'	232	1.2 lb
	6.0 mm	4' X 38'	152	1.8 lb
	8.0 mm	4' X 29'	116	2.3 lb
	9.5 mm	4' X 25'	96	2.7 lb

Tiles: 24" X 24"

Exloc interlocking tiles: 34.5" X 34.5"

**Thickness:** 4 mm, 6 mm, 8 mm, or 9.5 mm. Exloc tiles are available only in 8.0 and 9.5 mm thickness. Minimum quantities may be required.

<b>Density:</b>	ASTM D-792	Greater than 78 lbs/ft <sup>3</sup> .
<b>Aging Resistance:</b>	ASTM D-750	No Change
<b>Shore Hardness:</b>	ASTM D-2240	60 +/- 5
<b>Flammability:</b>	ASTM E-648	Class I
<b>Flame Spread:</b>	ASTM E-84	Class B
<b>Smoke Developed:</b>	ASTM E-84	Passes <450
<b>Ozone Exposure:</b>	ASTM D-1149-86	No adversities
<b>Storage:</b>	Rolls on end, minimum 55° F. Less than 50% humidity	

\* The above listed specifications are for 70% or greater EPDM formulations. Test Results will vary for those products with greater than 30% SBR content.

Reztec is a naturally resilient product with unparalleled durability, suitable for both commercial and residential installations. As with any flooring product, Reztec must be kept clean and dry to ensure its beauty throughout the life of the floor. Like any naturally pigmented product, Reztec colors can vary slightly between lots.

For more information about Expanko visit our website at [www.expanko.com](http://www.expanko.com) or contact Expanko at 800.345.6202. *Expanko since 1945.*